# SKYLINE COLLEGE


## STUDENT SUPPORT & COMMUNITY SERVICES CENTER AND SCIENCE ANNEX BUILDING

SAN MATEO COUNTY COMMUNITY COLLEGE DISTRICT - 3401 CSM DRIVE, SAN MATEO, CA.

FILE NO. 41-C1/APPL. NO. 01-106658

## DSA INCREMENT ONE SUBMITTAL

PROJECT RECORD DOCUMENTS



THE WORK INCLUDES CONSTRUCTION OF A NEW STAND ALONE 2 STORY STUDENT SUPPORT & COMMUNITY SERVICES CENTER AND A NEW 3 STORY SCIENCE ANNEX. BOTH BUILDINGS ARE IN THE CENTRAL CAMPUS AREA ADJACENT TO EXISTING STRUCTURES. THE NEW SCIENCE ANNEX IS DIRECTLY ADJACENT TO THE EXISTING SCIENCE BUILDING. BOTH NEW BUILDINGS WILL BE TYPE II, 1 HOUR RATED ADJACENT SITE AND LANDSCAPE WORK ARE ALSO PART OF THE PROJECT SCOPE. ALL NEW THE WORK IS BEING DESIGNED AND CONSTRUCTED AS A DESIGN/BUILD PROJECT. DUE TO SKYLINE'S REQUIREMENTS TO MEET THEIR EDUCATIONAL MASTER PLAN, FACILITIES MASTER PLAN AND BOND FUND COMMITMENTS, THE PROJECT IS BEING DIVIDED INTO 2 SEPARATE INCREMENTS FOR DSA REVIEW: . THE FIRST INCREMENT WILL BE A SUBMITTAL FOR THE FOUNDATION, SLAB ON GRADE, STRUCTURAL STEEL FRAMING AND METAL DECKS, AND ROUGH GRADING, 2. THE SECOND INCREMENTAL SUBMITTAL WILL INCLUDE ARCHITECTURAL, MECHANICAL, ELECTRICAL PLUMBING, CIVIL AND LANDSCAPE DOCUMENTS FOR EACH SEPARATE BUILDING TO COMPLETE THE

### APPLICABLE CODES

2001 BUILDING STANDARD ADMINISTRATION CODE.

2001 CALIFORNIA BUILDING CODE (CBC), PART 2, TITLE 24 C.C.R. (1997 UNIFORM BUILDING CODE VOLUMES 1-3 AND 2∞1 CALIFORNIA AMÉNDMENTS)

2001 CALIFORNIA ELECTRICAL CODE (CEC), PART 3, TITLE 24 C.C.R.; (1996 NATIONAL ELECTRICAL CODE AND 1996 CALIFORNIA AMENDMENTS) 2001 CALIFORNIA MECHANICAL CODE (CMC), PART 4, TITLE 24 C.C.R. ;

(1997 UNIFORM MECHANICAL CODE AND 2001 CALIFORNIA AMENDMENTS) 2001 CALIFORNIA PLUMBING CODE (CPC), PART 5, TITLE 24 C.C.R.

(1997 UNIFORM PLUMBING CODE AND 2001 CALIFORNIA AMENDMENTS) 2001 CALIFORNIA FIRE CODE (CFC), PART 9, TITLE 24 C.C.R. (1997 UNIFORM FIRE CODE AND 2001 CALIFORNIA AMENDMENTS)

2001 CALIFORNIA REFERENCED STANDARDS CODE

1990 TITLE 19,CCR, PUBLIC SAFETY, STATE FIRE MARSHALL REGULATIONS ANSI A156, 19-1984 AMERICAN NATIONAL STANDARD FOR POWER ASSIST AND LOW ENRGY POWER OPERATED DOORS

NFPA 13 - AUTOMATIC FIRE SPRINKLER SYSTEMS - 1999 EDITION

NFPA 24 - PRIVATE FIRE MAINS, - 1995 EDITION

(CALIFORNIA AMENDED) NFPA 72 - NATIONAL FIRE ALRM CODES - 1999 EDITION ADA - AMERICANS WITH DISABILITIES ACT, TITLE II: UNIFORM FEDERAL ACCESSIBLITY STANDARDS (UFAS) OR AMERICANS WITH DISABLITIES ACT ACCESSIBLITY GUIDELINES FOR BUILDINGS & FACILITIES (ADA AG)

#### ADMINISTRATIVE REQUIREMENTS

CHAPTER 4 PART 1, TITLE 24, CCR., ADMINISTRATIVE REQUIREMENTS (PARTIAL LISTING ONLY) 1. A COPY OF PARTS 1 AND 2, TITLE 24, C.C.R. SHALL BE KEPT ON THE JOB SITE AT ALL TIMES. 2. ALL CHANGE ORDERS AND ADDENDA TO BE SIGNED BY THE ARCHITECT AND THE OWNER AND APPROVED BY DSA. CHANGE ORDERS ARE NOT VALID UNTIL APPROVED BY DSA PER SECTION 4-335,

3. ALL TESTS TO CONFORM TO THE REQUIREMENTS OF SECTION 4-335, PART 1, TITLE 24, AND APPROVED

TESTS OF MATERIALS AND TESTING LABORATORY SHALL BE IN ACCORDANCE WITH SECTION 4-335 OF RT I, TITLE 24 AND THE DISTRICT SHALL EMPLOY AND PAY THE LABORATORY. COSTS OF RE-TEST AY BE BACK CHARGED TO THE CONTRACTOR. 5. DSA SHALL BE NOTIFIED AT THE START OF CONSTRUCTION AND PRIOR TO THE PLACEMENT OF CONCRETE PER SECTION 4-331, PART 1, TITLE 24.

6. INSPECTOR SHALL BE APPROVED BY DSA. INSPECTION SHALL BE IN ACCORDANCE WITH SECTION 4-333 (B). THE DUTY OF THE INSPECTOR SHALL BE IN ACCORDANCE WITH SECTION 4-342, PART I.

7. SUPERVISION OF CONSTRUCTION BY DSA SHALL BE IN ACCORDANCE WITH SECTION 4-334, PART I.

8. CONTRACTOR, INSPECTOR, ARCHITECT, AND ENGINEERS SHALL SUBMIT VERIFIED REPORTS (FORM SSS-6) IN ACCORDANCE WITH SECTION 4-336, AND 4-343, PART I, TITLE 24. 9. THE ARCHITECT AND THE STRUCTURAL ENGINEER SHALL PERFORM THEIR DUTIES IN ACCORDANCE WITH

10. THE CONTRACTOR SHALL PERFORM HIS DUTIES IN ACCORDANCE WITH SECTION 4-343, PART I, TITLE

SECTION 4-333 (A) AND 4-341, PART I, TITLE 24.

SHEET INDEX

FOR PEFERENCE ONLY

FOR REFERENCE ONLY

**COVER SHEET** ABBREVIATIONS, SYMBOLS, AND GENERAL NOTES ARCHITECTURAL SITE PLAN UTILITY PLAN BUILDING A - BUILDING CODE ANALYSIS AND EXITING PLAN BUILDING A - FIRST FLOOR PLAN **GENERAL NOTES GENERAL NOTES** 

TYPICAL DETAILS TYPICAL DETAILS TYPICAL STEEL DECK DETAILS TYPICAL DETAILS TYPICAL STEEL DETAILS TYPICAL STEEL DETAILS

SECTIONS AND DETAILS SECTIONS AND DETAILS SECTIONS AND DETAILS BRACE FRAME DETAILS BRACE FRAME CONNECTION DETAILS BASE PLATE DETAILS TYPICAL STAIR DETAILS TYPICAL STAIR DETAILS STAIR PLANS

MECHANICAL MECHANICAL SITE PLAN

STAIR PLANS

S11.2

BUILDING A - FIRST FLOOR PLUMBING PLAN BUILDING A - SECOND FLOOR UNDERGROUND PLUMBING PLAN

BUILDING B - FIRST FLOOR UNDERGROUND PLUMBING PLAN

SYMBOL LIST, GENERAL NOTES, INDEX

SINGLE LINE DIAGRAM A BUILDING A - SINGLE LINE DIAGRAMS BUILDING A - FIRST ELOOR POWER AND SIGNAL PLAN BUILDING A - SECOND FLOOR POWER AND SIGNAL PLAN

BUILDING B - SINGLE LINE DIAGRAMS BUILDING B - FIRST FLOOR POWER AND SIGNAL PLAN

FIRE ACCESS PLAN

THESE DRAWINGS AND/OR SPECIFICATIONS AND/OR CALCULATIONS FOR THE ITEMS LISTED BELOW HAVE BEEN PREPARED BY OTHER DESIGN PROFESSIONALS OR CONSULTANTS WHO ARE LICENSED AND/OR AUTHORIZED TO PREPARE SUCH DRAWINGS IN THIS STATE. THESE DOCUMENTS HAVE BEEN EXAMINED BY ME FOR DESIGN INTENT AND APPEAR TO MEET THE APPROPRIATE REQUIREMENTS OF TITLE 24, CALIFORNIA CODE OF REGULATIONS AND THE PROJECT SPECIFICATIONS PREPARED BY ME.

THE ITEMS LISTED BELOW HAVE BEEN COORDINATED WITH MY PLANS AND SPECIFICATIONS AND ARE ACCEPTABLE FOR INCORPORATION INTO THE CONSTRUCTION OF THIS PROJECT FOR WHICH I AM THE INDIVIDUAL DESIGNATED TO BE IN GENERAL RESPONSIBLE CHARGE.

\* CIVIL SHEETS: CO TO C6 SERIES \* MECHANICAL SHEETS: MA AND MB SERIES \* PLUMBING SHEETS: PA AND MB SERIES \* ELECTRICAL SHEETS: EO, EA AND ED SENOLS

\* LANDSCAPE SHEETS: L SERVES \* STRUCTURE HEETS: S SERIES

Mick - Contects C13447

File # 41-01 IDENTIFICATION STAMP DIV. OF THE STATE ARCHITECT OFFICE OF REGULATION SERVICES

SHEET NUMBER

A0.00

2. TYPICAL DETAILS AND NOTES ON THESE SHEETS SHALL APPLY UNLESS SPECIFICALLY SHOWN OR NOTED OTHERWISE. DETAILS NOT FULLY SHOWN OR NOTED SHALL BE SIMILAR TO DETAILS SHOWN FOR SIMILAR CONDITIONS.

3. IT SHALL BE THE CONTRACTOR'S SOLE RESPONSIBILITY TO DESIGN AND PROVIDE ADEQUATE SHORING, BRACING AND FORMWORK, ETC., AS REQUIRED FOR THE PROTECTION OF LIFE AND PROPERTY DURING THE CONSTRUCTION OF THIS BUILDING. SHORING AND BRACING SHALL REMAIN IN PLACE UNTIL FLOORS, ROOF AND WALL SHEATHING HAVE BEEN ENTIRELY CONSTRUCTED SHORING DRAWINGS AND CALCULATIONS SHALL BE SEALED BY REGISTERED ENGINEER AND SUBMITTED TO ARCHITECT/ENGINEER FOR REVIEW.

4. THE CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS WITH THE ARCHITECTURAL, CIVIL, ELECTRICAL AND MECHANICAL DRAWING BEFORE PREPARING SHOP DRAWINGS, FABRICATION OR CONSTRUCTION. SEE ARCHITECTURAL, ELECTRICAL AND MECHANICAL DRAWINGS FOR SIZE AND LOCATIONS OF PIPES. SLEEVES. PITS. VENTS. DUCTS. ETC. AND DETAILS NOT SHOWN ON THE STRUCTURAL DRAWINGS.

5. CONSTRUCTION MATERIAL SHALL BE SPREAD OUT IF PLACED ON FRAMED ROOF OR FLOOR. LOAD SHALL NOT EXCEED THE DESIGN LIVE LOAD PER SQUARE FOOT. PROVIDE ADEQUATE SHORING AND/ OR BRACING WHERE STRUCTURE HAS NOT ATTAINED DESIGN

6. ALL DRAWINGS ARE CONSIDERED TO BE A PART OF THE CONTRACT DOCUMENTS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REVIEW AND COORDINATION OF ALL DRAWINGS AND SPECIFICATIONS PRIOR TO THE START OF CONSTRUCTION. ANY DISCREPANCIES THAT OCCUR SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT PRIOR TO START OF CONSTRUCTION SO THAT A CLARIFICATION CAN BE ISSUED. ANY WORK PERFORMED IN CONFLICT WITH THE CONTRACT DOCUMENTS OR ANY CODE REQUIREMENTS SHALL BE CORRECTED BY THE CONTRACTOR AT THEIR OWN EXPENSE AND AT NO EXPENSE TO THE OWNER OR ARCHITECT.

7. NOTES AND DETAILS ON DRAWINGS SHALL TAKE PRECEDENCE OVER GENERAL NOTES AND TYPICAL DETAILS. WHERE NO DETAILS GIVEN, CONSTRUCTION SHALL BE AS SHOWN FOR SIMILAR WORK.

8. THE CONTRACT STRUCTURAL DRAWINGS AND SPECIFICATIONS REPRESENT THE FINISHED STRUCTURE. THEY DO NOT INDICATE THE METHOD OF CONSTRUCTION. THE CONTRACTOR SHALL PROVIDE ALL MEASURES NECESSARY TO PROTECT THE STRUCTURE DURING CONSTRUCTION. SUCH MEASURES SHALL INCLUDE, BUT NOT BE LIMITED TO, BRACING, SHORING FOR LOADS DUE TO CONSTRUCTION EQUIPMENT. ETC. OBSERVATION VISITS TO THE SITE BY THE STRUCTURAL ENGINEER SHALL NOT INCLUDE INSPECTION OF THE ABOVE ITEMS.

9. OPENINGS, POCKETS, ETC., LARGER THAN 6" SHALL NOT BE PLACED IN CONCRETE SLABS, DECKS, WALLS, UNLESS SPECIALLY DETAILED ON THE STRUCTURAL DRAWINGS. NOTIFY THE STRUCTURAL ENGINEER WHEN DRAWINGS BY OTHERS SHOW OPENINGS, POCKETS, ETC., LARGER THAN 5" NOT SHOWN ON THE STRUCTURAL DRAWINGS, BUT WHICH ARE LOCATED IN STRUCTURAL MEMBERS. FOR ANY FURTHER RESTRICTIONS ON OPENINGS IN STRUCTURAL ELEMENTS, SEE APPLICABLE SECTIONS

10. PIPES LARGER THAN 1 1/2" DIAMETER SHALL NOT BE EMBEDDED IN STRUCTURAL CONCRETE EXCEPT WHEN WHERE SPECIFICALLY APPROVED. NO CONDUITS SHALL BE PLACED IN CONCRETE FILL OVER METAL

DESIGN BASIS REFERENCE CODE

2001 CALIFORNIA BUILDING CODE "STATE CHAPTERS" LIVE LOADS

-20 PSF (REDUCIBLE) FLOOR: ALL TYPICAL FLOOR AREAS SUCH -80 PSF (REDUCIBLE) AS MEETING ROOMS, OFFICE SPACE, KITCHEN, ETC., UNLESS NOTED OTHERWISE STORAGE ROOMS -125 PSF (NO REDUCTION)

PATIOS AND EXTERIOR AREAS ACCESSIBLE -100 PSF (NO REDUCTION) TO THE PUBLIC ASSEMBLY AREAS -100 PSF (NO REDUCTION) DINING AREAS (NOT USED FOR ASSEMBLY -100 PSF (REDUCIBLE)

EXITS/ CORRIDORS -100 PSF (NO REDUCTION) PARTITION LOADS TYPICAL FLOOR

.....SEE MECHANICAL SCHEDULES EQUIPMENT..... TYPICAL FLOOR (SEISMIC ONLY)......10.0 PSF ...2001 CBC SECTION 1630A.1 EARTHQUAKE LOADS.. E=PE<sub>h</sub>± E<sub>v</sub> E<sub>m</sub>= 1. E<sub>h</sub>

WHERE: E, DUE TO

AND: SOIL TYPE= Sp

 $V = \frac{2.5 \text{ Ca I}}{2} \text{ W}$  (NOT TO EXCEED) V= 0.11 Ca | W (SHALL NOT BE LESS THAN)

V = 0.8 ZNVI W (NOT TO EXCEED FOR ZONE 4)

Z = ZONE 4= 1.15....FOR STUDENT CENTER BUILDING | = 1.00....FOR SCIENCE ANNEX BUILDING R = 5.5 ....FOR CONCRETE SHEAR WALLS

R = 6.4 ....STEEL SPECIAL CONCENTRIC BRACE FRAME R = 8.5 ....STEEL SPECIAL MOMENT RESISTING FRAMES Na= 1.5 ....FOR STUDENT CENTER BUILDING Na= 1.5 ....FOR SCIENCE ANNEX BUILDING

Ca= 0.66....FOR STUDENT CENTER BUILDING

Ca= 0.66....FOR SCIENCE ANNEX BUILDING Cv = 1.28W = TOTAL SEISMIC DEAD LOAD

....2001 CBC SECTION 1615A. ....SECTION 1620A P=Ce Cq qs lw..... Ce= SEE TABLE 16A-G FOR EXPOSURE "C Cg= SEE TABLE 16A-H qs= 16.4 PSF FOR BASIC WIND SPEED =80MPH

**FOUNDATIONS** FOUNDATION DESIGN IS BASED ON A GEOTECHNICAL REPORT BY LOWNEY & ASSOCIATES. NO. 324-29 DATED JULY 17TH. 2003.

AND SUPPLEMENTAL REPORT #324-29A DATED NOV 8, 2004 AND SUPPLEMENTAL REPORT #1620-30 DATED FEB 28,2005. 2. IT IS RECOMMENDED THAT SOIL ENGINEERS a) REVIEW THE

FOUNDATION PLANS PRIOR TO CONSTRUCTION, AND b) OBSERVE THE INSTALLATION OF THE FOUNDATION.

3. ANY SLOPES SHALL BE CONSTRUCTED AT A MAXIMUM GRADIENT OF 1.25:1 (HORIZONTAL TO VERTICAL). FILL AND CUT SLOPES SHOULD BE VEGETATED AS SOON AS POSSIBLE TO MINIMIZE EROSION OF SOIL. SEE GEOTECHNICAL REPORT FOR ADDITIONAL INFORMATION. SEE CIVIL DWGS FOR BUILDING PAD SECTION.

4. ANY VERTICAL SOIL CUTS MUST BE PROVIDED WITH PROPER SHORING TO PROTECT THE WORKERS AND ADJACENT PROPERTY. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR ALL EXCAVATION PROCEDURES INCLUDING LAGGING, SHORING, AND THE PROTECTION OF ADJACENT PROPERTY, STRUCTURES, STREETS AND UTILITIES. ALL WORK AND CONSTRUCTION SHALL COMPLY WITH ALL APPLICABLE BUILDING CODES, CALIFORNIA OSHA REGULATIONS AND SAFETY REQUIREMENTS.

AN ADEQUATE DRAINAGE SYSTEM SHALL BE PROVIDED TO COLLECT AND TRANSPORT RUNOFF WATER TO THE DISCHARGE FACILITIES. ALL RETAINING WALLS SHALL HAVE AT THE BOTTOM, PERFORATED BACK-OF WALL DRAINS AND WEEP HOLES AT 6'-0" O.C. MAXIMUM.

6. ALL BUILDING PADS SHALL BE CONSTRUCTED IN ACCORDANCE WITH GEOTECHNICAL REPORTS REFERRED TO IN NOTE # 1 ABOVE

7. COMPACTION OF OVER EXCAVATION & FILL MATERIAL SHALL BE IN ACCORDANCE WITH THE GEOTECHNICAL REPORT REFERRED TO IN NOTE #1 ABOVE.

8. SOIL PRESSURES USED FOR FOUNDATION DESIGN SHALL BE AS FOLLOWS:

A) ALLOWABLE BEARING OF CONTINUOUS & SPREAD FOOTINGS Q = 3000 PSFQ = 4500 PSF

B) LATERAL EARTH PRESSURES UN-RESTRAINED (DRAINED CONDITION)=45 PCF+1/3 SURCHARGE RESTRAINED (DRAINED CONDITION) = 45PCF+8H+1/2 SURCHARGE

Q = 6000 PSF

DL+LL+ST

C) FRICTIONAL RESISTANCE ALLOWABLE = 0.3

D) PASSIVE PRESSURES 300 PCF ALLOWABLE =

E) SEE GEOTECHNICAL REPORT FOR ADDITIONAL LATERAL EARTH PRESSURE REQUIREMENTS FOR RETAINING WALLS.

9. CONTRACTOR TO PROVIDE FOR DE-WATERING OF EXCAVATIONS FROM FITHER SURFACE WATER. GROUND WATER OR SEEPAGE, IF REQUIRED.

10. FOOTING WILL BE INCREASED 2 IN. IN WIDTH FROM THAT SHOWN ON PLANS. 257 54 Cout Batch Plant inspection wet Recurred

CONCRETE 1. THE MINIMUM 28 DAY STRENGTH AND TYPE OF CONCRETE SHALL BE AS FOLLOWS:

SLABS ON GRADE (INTERIOR). ..150 PCF. f'c = 3000 PSI ..150 PCF. f'c = 3000 PSI FOUNDATIONS COLUMNS, BEAMS, SUSPENDED SLAB, WALLS.....150 PCF. f'c = 4000 PSI LIGHTWEIGHT CONCRETE TOPPING SLABS.......110 PCF. f'c = 3000 PSI MECHANICAL CURBS AND PADS @ GRADE......150 PCF. f'c = 3000 PSI MECHANICAL CURBS AND PADS @ ...110PCF. F'c = 3000 PSI2ND FLR & ROOF.... CONCRETE TOPPING AT STAIR TREADS .110 PCF. f'c = 3000 PSIAND PLATFORMS..... ..150 PCF. f'c = 3000 PSI OTHER..... \* W/C RATIO SHALL HOT EXCEED 0.45

2. DIMENSIONS SHOWN FOR LOCATION OF REINFORCING ARE TO THE FACE OF MAIN BARS, TIES, ETC. AND DENOTE CLEAR COVERAGE. CONCRETE COVERAGE SHALL BE AS FOLLOWS, U.O.N. ON DRAWINGS:

A) CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH ALL ELEMENTS .

B) CONCRETE EXPOSED TO EARTH OR WEATHER BUT PLACED IN FORMS. #6 THROUGH #18 BARS. .....1 1/2" #5 BARS, W31 OR D31 WIRE, AND SMALLER.....

 C) CONCRETE NOT EXPOSED TO WEATHER OR IN CONTACT WITH GROUND SLABS, WALLS OR JOISTS. #14 OR #18 BARS..... #11 BARS AND SMALLER.. BEAMS AND COLUMNS. SHELLS AND FOLDED PLATE MEMBERS

#5 BARS, W31 OR D31 WIRE, AND SMALLER..... 3. NO PIPES OR DUCTS SHALL BE PLACED IN CONCRETE SLABS OR WALLS UNLESS SPECIFICALLY DETAILED.

#6 AND LARGER BARS......

4. REFER TO ARCHITECTURAL, STRUCTURAL, ELECTRICAL AND MECHANICAL DRAWINGS FOR ALL MOULDS, GROOVES, ORNAMENTS, CLIPS AND GROUNDS TO BE CAST IN CONCRETE.

5. FORMS SHALL BE PROPERLY CONSTRUCTED CONFORMING TO CONCRETE SURFACE AS SHOWN ON THE DRAWINGS, SUFFICIENTLY TIGHT TO PREVENT LEAKAGE, SUFFICIENTLY STRONG AND BRACED TO MAINTAIN THEIR SHAPE AND ALIGNMENT UNTIL NO LONGER NEEDED TO SUPPORT THE CONCRETE.

6. HORIZONTAL CONSTRUCTION JOINTS SHALL BE LOCATED AS SHOWN ON THE DRAWINGS, AND THE HARDENED CONCRETE SURFACE SHALL BE CLEANED BY SAND-BLASTING OR OTHER APPROVED MEANS TO EXPOSE FIRMLY EMBEDDED AGGREGATES PRIOR TO POURING ADDITIONAL CONCRETE IN CONTACT WITH THESE SURFACES. VERTICAL CONSTRUCTION JOINTS CONFORM TO ALL PLANS AND DETAILS

FORMS AND SHORING SHALL NOT BE REMOVED UNTIL THE CONCRETE HAS ATTAINED SUFFICIENT STRENGTH TO WITHSTAND ALL LOADS TO BE IMPOSED WITHOUT EXCESSIVE STRESS, CREEP OR DEFLECTION. 8. ALL ITEMS TO BE CAST IN CONCRETE SUCH AS REINFORCING,

DOWELS, BOLTS, ANCHORS, PIPES, SLEEVES, ETC. SHALL BE

SECURELY POSITIONED IN THE FORMS BEFORE PLACING THE

9. SEE ARCHITECTURAL, ELECTRICAL, AND MECHANICAL DRAWINGS FOR SIZE AND LOCATION OF PIPES, SLEEVES, PITS AND DETAILS NOT SHOWN ON THESE STRUCTURAL DRAWINGS. ALL DIMENSIONS ARE TO BE CHECKED AND VERIFIED WITH THE ARCHITECTURAL,

ELECTRICAL AND MECHANICAL DRAWINGS. 10. MINIMUM EMBEDMENT FOR ANCHOR BOLTS IN CONCRETE SHALL BE

9", UNLESS SPECIFICALLY NOTED OTHERWISE. 11. THE CONTRACTOR SHALL INFORM THE ARCHITECT/ENGINEER AT LEAST 2 DAYS PRIOR TO POURING ANY STRUCTURAL CONCRETE SO

THAT HE MAY HAVE THE OPPORTUNITY OF REVIEWING THE WORK

PRIOR TO PLACEMENT 12. BARS SHALL BE CLEAN OF RUST, GREASE, OR OTHER MATERIALS LIKELY TO IMPAIR BOND. ALL REINFORCING BAR BENDS SHALL BE

13. REINFORCING BAR SPLICES SHALL BE MADE AS INDICATED ON THE DRAWINGS. MINIMUM SPLICE LENGTH FOR REINFORCING STEEL BARS IN MASONRY SHALL BE 48 BAR DIAMETERS, 24" MINIMUM. MINIMUM SPLICE LENGTH FOR REINFORCING STEEL BARS IN CONCRETE SHALL BE AS PER THE CODE SECTION 1912A. LAP ALL HORIZONTAL BARS AT CORNERS AND INTERSECTIONS. STAGGER ALL SPLICES

UNLESS NOTED OTHERWISE ON PLANS. 14. ALL BARS SHALL BE MARKED SO THEIR IDENTIFICATION CAN BE MADE WHEN THE FINAL IN-PLACE INSPECTION IS MADE.

15. WHERE WELDING OF REINFORCING IS APPROVED BY THE STRUCTURAL ENGINEER, IT SHALL BE DONE BY AWS CERTIFIED WELDERS USING E90XX OR APPROVED ELECTRODES. WELDING PROCEDURES SHALL CONFORM TO THE REQUIREMENTS OF STRUCTURAL WELDING CODE-REINFORCING STEEL, AWS-D1.4, LATEST REVISION. REINFORCING BARS TO BE WELDED SHALL CONFORM TO THE REQUIREMENTS OF

16. LIGHTWEIGHT CONCRETE SHALL CONFORM TO ASTM-C330 DRYING SHRINKAGE OF TEST SPECIMENS SHALL NOT EXCEED 0.07%.

REINFORCING STEEL 1. ALL REINFORCING STEEL SHALL BE NEW STOCK DEFORMED BARS CONFORMING TO ASTM A-615 GRADE 40 FOR #3 BARS ASTM A-615 GRADE 60, FOR #4 AND LARGER UNLESS OTHERWISE

2. WELDED WIRE FABRIC SHALL CONFORM TO ASTM A-185. WELDED WIRE TO BE SUPPLIED IN FLAT SHEETS ONLY.

NOTED. USE ASTM A-706 FOR ALL WELDED APPLICATIONS.

ALL BARS SHALL HAVE A MINIMUM "LAP SPLICE" OR "DEVELOPMENT LENGTH" PER APPROPRIATE TABLES ON THIS SHEET, UNLESS OTHERWISE NOTED.

4. REINFORCING SPACINGS GIVEN ARE MAXIMUM ON CENTER AND ALL REINFORCING IS CONTINUOUS UNLESS OTHERWISE NOTED.

5. ALL REINFORCING STEEL SHALL BE SECURELY WIRED AND PROPERLY SUPPORTED ABOVE GROUND AND AWAY FROM THE FORM.

6. REINFORCING BAR FABRICATION LAPS AND PLACING SHALL CONFORM TO THE MANUAL OF STANDARD PRACTICE OF THE WESTERN CONCRETE REINFORCING STEEL INSTITUTE, UNLESS OTHERWISE NOTED ON DRAWINGS.

BEAMS, ETC. AS FOLLOWS: TOP BARS AT MID-SPAN. BOTTOM BARS

Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in any way. If an item in this document is altered, the alteration of the law for any person, unless acting under the direction of the alteration.

7. DOWEL ALL VERTICAL REINFORCING IN WALLS AND COLUMNS FROM FOUNDATION WITH THE SAME SIZE REINFORCING. (U.O.N.)

8. SPLICES IN ADJACENT BARS SHALL BE NOT LESS THAN 5'-0" APART. 9. SPLICE CONTINUOUS BARS IN SPANDRELS. GRADE BEAMS, WALL

AT CENTERLINE SUPPORT (U.O.N.)

STRUCTURAL STEEL

ALL FABRICATION AND ERECTION SHALL CONFORM TO THE AISC SPECIFICATIONS AND AMERICAN IRON AND STEEL SPECIFICATION MANUAL (LATEST EDITION). THE DESIGN AND ERECTION OF LIGHT GAGE STEEL STRUCTURAL MEMBERS SHALL CONFORM TO AISI (LATEST EDITION), EXCEPT AS NOTED OR AS REQUIRED BY THE CALIFORNIA BUILDING CODE. WELDING SHALL CONFORM TO THE AWS SPECIFICATIONS.

2. WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE BEST PRACTICE AND WITHIN THE TOLERANCES SPECIFIED IN THE AISC SPECIFICATIONS FOR STRUCTURAL STEEL.

IT IS SPECIFICALLY NOTED THAT BURNED HOLES ARE NOT ACCEPTABLE UNLESS SPECIAL PERMISSION IS GIVEN BY ENGINEER.

4. ALL SHOP FABRICATED WORK SHALL BE DONE IN A SHOP APPROVED BY THE GOVERNING AGENCY. FABRICATOR SHALL SUBMIT PROGRAM OF WELDING INSPECTION TO ENGINEER FOR APPROVAL.

5. ALL STRUCTURAL STEEL SHALL BE AS FOLLOWS UNO: ASTM A992 GRADE 50 ALL WF, WT SHAPES ... BASE PL, CONN. PL & MISC STEEL (UNO)... ASTM A36 MOMENT FRAME COLUMNS... .ASTM A992 GRADE 50 ASTM A572 GRADE 50 GUSSET & COLLECTOR PLATES.

.. ASTM A53 GRADE B.

.ASTM A500 GRADE B.

.ASTM A36

6. ALL HIGH STRENGTH BOLTS SHALL BE ASTM A325-N TYPE UNLESS OTHERWISE NOTED. ALL ASTM A325-SC & A490-SC BOLTS SHALL BE FULLY TENSIONED.

PIPE COLUMNS (TYPE S, SEAMLESS).

STRUCTURAL TUBING..

ANGLE, CHANNELS ...

7. ALL BOLTS USED FOR ERECTION SHALL BE ASTM A307 TYPE WITH THREADS EXCLUDED FROM SHEAR PLANES. 8. ALL PLAIN ANCHORS SHALL BE A36; ALL ANCHOR BOLTS SHALL

COMPLY WITH ASTM A307. 3" MINIMUM CONCRETE COVER WILL BE PLACED AROUND ALL ANCHOR BOLTS EXPOSED TO THE WEATHER, U.N.O. 9. WELDING MATERIALS: AWS D1.1: TYPE REQUIRED FOR MATERIALS

BEING WELDED. 10. PROVIDE CONTINUOUS INSPECTION FOR ALL FABRICATION AND WELDING OF STRUCTURAL STEEL IN ACCORDANCE WITH CODE REQUIREMENTS. ALL COMPLETE PENETRATION GROOVE WELDS IN JOINTS AND SPLICES SHALL BE TESTED 100 PERCENT IN ACCORDANCE WITH CBC SEC. 1701B5.1. USE ONE OF THE

 A WELDING SEQUENCE SHALL BE PLANNED TO MINIMIZE RESIDUAL STRESSES AND DISTORTIONS OF INDIVIDUAL MEMBERS AND THE BUILDING FRAME. ALL DETAILING, FABRICATION, AND ERECTION SHALL COMPLY WITH AISC, LATEST EDITION.

APPROVED METHODS OF TIGHTENING HIGH STRENGTH BOLTS

UNLESS OTHERWISE NOTED, ALL STIFFENER PLATES ARE 3/8" THICK MINIMUM AND ALL BUTT WELDS ARE FULL PENETRATION WELDS. ERECTION CLIPS, TEMPORARY BRACING, ETC., REQUIRED BY THE CONTRACTOR ARE NOT SHOWN.

of clock best plate acceptable to be 1/2" partial pene SUBMIT SHOP DRAWINGS FOR THE FABRICATION AND ERECTION OF ALL ASSEMBLIES OF STRUCTURAL STEEL WORK. INCLUDE PLANS AND ELEVATIONS AT NOT LESS THAN 1" TO 1'-0" SCALE, AND INCLUDE DETAILS OF SECTIONS AT NOT LESS THAN 3" TO 1'-0" SCALE.

NO WORK OR FABRICATION SHALL BE COMMENCED OR MATERIAL DELIVERED TO THE JOB UNTIL THE ENGINEER HAS REVIEWED AND APPROVED THE SHOP DRAWINGS. ALL STRUCTURAL STEEL SHALL BE PAINTED WITH ONE SHOP COAT

OF ZINC CHROMATE PRIMER OR EQUAL. AFTER ERECTION, FIELD CONNECTIONS SHALL BE TOUCHED UP. DO NOT PAINT PORTION OF STEEL TO BE EMBEDDED IN CONCRETE, HEADED ANCHOR STUDS, OR AREAS TO RECEIVE FIRE PROOFING. WELD LENGTHS CALLED FOR ON PLANS ARE THE NET EFFECTIVE LENGTH REQUIRED. WHERE FILLET WELD SYMBOL IS GIVEN

SPECIFIED IN AISC MANUAL OF STEEL CONSTRUCTION 9TH EDITION, **SECTION 1.17.2** 17. THE USE OF E70T-4 WELDING WIRE IS NOT ALLOWED FOR ANY

WITHOUT INDICATION OF SIZE. USE MINIMUM SIZE WELDS AS

WRITTEN WELDING PROCEDURE SPECIFICATIONS (WPS) PER THE RECOMMENDATIONS OF THE AMERICAN WELDING SOCIETY (AWS) SHALL BE DEVELOPED BY THE FABRICATOR/ERECTOR AND SUBMITTED FOR REVIEWED TO THE ENGINEER PRIOR TO ANY WELDING OF THE STRUCTURAL STEEL. THE WELDING PROCEDURES SHALL INCLUDE ALL THE WELDED JOINTS AND CONFIGURATIONS TO BE USED ON THIS PROJECT-ONLY WPS WHICH ARE RELEVANT TO THIS PROJECT SHALL BE SUMITTED. ALL WELDED JOINTS SHALL BE PRE-QUALIFIED PER AWS OR BE QUALIFIED BY TEST PER AWS A PROCEDURE QUALIFICATION RECORD (PQR) SHALL BE INCLUDED WITH THE WPS IF THE WELDING PROCEDURE OR JOINT IS QUALIFIED BY TESTING. THE ELECTRODE MANUFACTURER AND PRODUCT/TRADE NAME SHALL BE IDENTIFIED IN THE WPS IN ADDITION TO THE AWS ELECTRODE CLASSIFICATION NAME. A COPY OF THE ELECTRODE MANUFACTURER'S TECHNICAL DATA SHEETS WITH THE RECOMMENDED WELDING PARAMETERS SHALL BE SUBMITTED WITH THE WPS.

19. ALL WELDS USED IN PRIMARY MEMBERS AND CONNECTIONS IN THE LATERAL FORCE-RESISTING SYSTEMS SHALL BE MADE WITH A FILLER METAL THAT HAS A MINIMUM CHARPY V-NOTCH TOUGHNESS OF 20 FT-LBS AT MINUS 20 DEGREES F, AS DETERMINED BY AWS CLASSIFICATION OR MANUFACTURER CERTIFICATION. THIS INCLUDES ALL WELDS THAT CONNECT PLATES, SHEAR TABS STIFFENER PLATES, TUBE STEEL OR WX BRACES, GUSSET PLATES, AND CHORDS / COLLECTORS.

HEADED STUDS

ALL HEADED STUDS WELDED TO BEAMS OR CONCRETE CONNECTIONS SHALL BE "TRUE-WELD STUDS", DIVISION OF TRU-FIT SCREW CORPORATION, CLEVELAND, OHIO OR "NELSON STUD", TRW FASTENERS AND ASSEMBLIES GROUP, LORAIN, OHIO, OR

APPROVED EQUAL. ALL HEADED STUDS SHALL BE AUTOMATICALLY END WELDED IN SHOP OR FIELD WITH EQUIPMENT RECOMMENDED BY MANUFACTURER

STEEL SHEAR STUDS MATERIAL WELDING AND INSPECTION, SHALL BE IN ACCORDANCE WITH AWS "STRUCTURAL WELDING CODE" AWS D1.1-88, SECTION 7. ALL STUDS SHALL BE 3/4" DIAMETER X 5" LONG, SPACED AT 12" o.c. MAXIMUM, UNLESS NOTED OTHERWISE.

UNLESS OTHERWISE NOTED ON THE DRAWINGS ROOF DECKING SHALL BE AS MANUFACTURED BY VERCO MANUFACTURING INC. (ICBO REPORT ER-2078P), OR EQUAL AS APPROVED BY THE

ENGINEER OF RECORD. SEE SECTION 01330. THE MINIMUM BASE THICKNESS OF METAL MATERIAL SHALL BE AS NOTED ON PLANS.

FURNISH DECKING IN MINIMUM LENGTHS OF THREE SPANS EXCEPT WHERE SINGLE OR DOUBLE SPANS ARE INDICATED ON THE DRAWINGS. STRUCTURAL PROPERTIES SHALL BE EQUAL TO THOSE OF THE

DECKING TYPES INDICATED ON THE DRAWINGS AS APPROVED BY FURNISH ALL ACCESSORIES REQUIRED TO PROVIDE A COMPLETE INSTALLATION INCLUDING FILLERS FOR END PANELS, FRICTION CAPS FOR CLOSING SHOP FABRICATED ACCESS HOLES FOR WELDING, FLASHING AT COLUMNS AND CLOSURES FOR CELL ENDS, ROOF AND FLOOR DRAIN RECESSES, AND OTHER ACCESSORIES AS

REQUIRED. ACCESSORIES SHALL BE FORMED FROM GALVANIZED STANDARD COMMERCIAL GRADE STEEL OR BETTER. WELDING ROD: ASW A5.1—LATEST EDITION, E90XX, LOW HYDROGEN. SHEAR STUDS, INCLUDING INSTALLATION EQUIPMENT SHALL BE AS MANUFACTURED BY NELSON STUD WELDING DIVISION, GREGORY

INDUSTRIES, LORAIN, OHIO, TYPES S3L OR H4L, OR EQUAL

APPROVED IN ACCORDANCE WITH SECTION 01330, AND SHALL

CONFORM TO AWS D1.1 (LATEST EDITION). FERRULES SHALL BE SUITABLE FOR USE WITH GALVANIZED METAL DECK WHERE INDICATED. WHERE LARGE PREDETERMINED OPENINGS FOR DUCTS AND SIMILAR ELEMENTS PASSING THROUGH THE PANEL UNITS OCCUR. FURNISH PREFABRICATED UNITS TO FIT JOB CONDITIONS: WHERE OTHER HOLES OR OPENING ARE REQUIRED IN DECKING AFTER ERECTION, SUCH HOLES SHALL BE REINFORCED

PER THE DRAWINGS. PROVIDE ALL CLOSURES, END PLATES, PROFILE PLATES AND OTHER ACCESSORIES REQUIRED FOR A COMPLETE INSTALLATION.

WELD IN PLACE. SUPPORT AT COLUMNS: WHERE, DUE TO CUTTING OF DECK UNITS AT COLUMNS, BEARING SUPPORT IS NOT PROVIDED FOR THE END OF A WEB, SUCH WEB SHALL BE WELDED TO THE COLUMN OR STRUCTURAL STEEL MATERIAL AT THE COLUMN OR EQUIVALENT SUPPORT SHALL BE PROVIDED. THE WELDING OR EQUIVALENT SUPPORT SHALL BE SUFFICIENT FOR THE SUPPORT OF THE DECK, CONSTRUCTION LOADS. PROVIDE L3x3x1/4 MINIMUM WITH A 3/16" CONTINUOUS FILLET WELD FOR SUPPORT AT SUCH LOCATIONS. 11. SUBMIT SHOP DRAWINGS FOR THE FABRICATION AND ERECTION OF

ALL ASSEMBLIES IN ACCORDANCE WITH THE SPECIFICATIONS.

NO WORK OF FABRICATION SHALL BE COMMENCED OR MATERIAL DELIVERED TO THE JOB UNTIL THE ENGINEER HAS REVIEWED AND APPROVED THE SHOP DRAWINGS.

ALL CONCRETE AT METAL DECK ASSEMBLIES SHALL BE REINFORCED WITH A MINIMUM OF WELDED WIRE FABRIC 4x4 W5x5.

MASONRY NOTES

SPECIAL MASONRY INSPECTION IS REQUIRED FOR ALL BLOCK INSTALLATION. CEMENT SHALL BE PORTLAND CEMENT CONFORMING TO CBC SECTION 2102A.2.2 TYPE I OR TYPE II, AND SHALL BE ENTIRELY OF ONE

WATER USED FOR MORTAR AND GROUT SHALL BE CLEAN AND FREE FROM DELETERIOUS AMOUNTS OF ACIDS, SALTS, ALKALI, AND ORGANIC MATERIALS.

4. HYDRATED LIME SHALL CONFORM TO CBC SECTION 2102A.2.3.2, TYPE S. AGGREGATES: SAND FOR MORTAR SHALL CONFORM TO ASTM C-144 EXCEPT THAT NOT LESS THAN 3% OF THE SAND SHALL PASS THE NUMBER 100 SIEVE. SAND AND PEA GRAVEL FOR GROUT SHALL CONFORM TO ASTM C-404-61, TABLE I. COARSE AGGREGATE. EXCEPT WHEN OTHER GRADINGS ARE SPECIFICALLY APPROVED BY THE ENGINEER.

CONCRETE MASONRY UNITS SHALL BE HOLLOW, SUITABLE FOR BEARING WALL CONSTRUCTION. ALL BLOCKS SHALL BE GRADE N-1 AND CONFORM TO CBC SECTION 2102A.2.5.2. IN ADDITION, UNITS SHALL HAVE A LINEAR SHRINKAGE OF 0.067% MAXIMUM FROM SATURATED TO THE OVEN DRY CONDITION. MASONRY UNITS SHALL HAVE CURED FOR NOT LESS THAN 28 DAYS WHEN PLACED IN THE STRUCTURE. BLOCKS COLOR SHALL BE APPROVED BY THE ARCHITECT. NET COMPRESSIVE STRESS OF MASONRY UNITS SHALL BE 1900 PSI (F'm OF GROUT, BLOCK, AND MORTAR ASSEMBLY= 1500 PSI.)

ADMIXTURES: THE USE OF ADMIXTURES SHALL NOT BE PERMITTED IN MORTAR OR GROUT UNLESS SUSTAINING DATA HAS BEEN SUBMITTED TO AND APPROVED BY THE ENGINEER. THE USE OF ADMIXTURES IN MORTAR SHALL BE ONLY AS APPROVED BY THE FNGINFER. THE USE OF UNCONTROLLED FIRE CLAY, DIRT, AND OTHER DELETERIOUS MATERIALS IS PROHIBITED.

8. MORTAR SHALL BE TYPE "S", 1900 psi MINIMUM

GROUT SHALL DEVELOP A MINIMUM COMPRESSIVE STRENGTH OF 2000 psi AT 28 DAYS. APPROVED ADMIXTURES MAY BE ADDED TO THE GROUT, COARSE GROUT SHALL BE USED IN ALL GROUT SPACES 2" OR MORE IN WIDTH AND ALL FILLED CELL

CONSTRUCTION. RFL 55 sack Not acceptable GROUT FOR PUMPING SHALL BE FLUID CONSISTENCY AND SHALL NOT HAVE LESS THAN (7) SACKS OF CEMENT IN EACH CUBIC YARD OF GROUT. THE MIX SHALL BE AS APPROVED BY ENGINEER. FLUID CONSISTENCY SHALL MEAN A CONSISTENCY AS FLUID AS POSSIBLE FOR POURING, WITHOUT SEGREGATION OF THE CONSTITUENT PARTS.

ALL WALLS SHALL HAVE ALL CELLS FILLED SOLID WITH GROUT. ALIGNMENT OF VERTICAL CELLS: ALL MASONRY SHALL BE BUILT TO PRESERVE THE UNOBSTRUCTED VERTICAL CONTINUITY OF THE CELLS TO BE FILLED. THE VERTICAL ALIGNMENT SHALL BE SUFFICIENT TO MAINTAIN A CLEAR, UNOBSTRUCTED VERTICAL FLUE MEASURING NOT LESS THAN 3" BY 3". EXCEPT WHERE OPEN END UNITS ARE USED.

LAYING: IN PLACING MORTAR IN HORIZONTAL JOINTS, COMPLETELY COVER THE FACE SHELLS OF THE UNITS WITH MORTAR, SOLIDLY FILL ALL HEAD JOINTS. LAY ALL MASONRY IN COMMON BOND. HOLD RACKING TO A MINIMUM. NO TOOTHING SHALL BE ALLOWED.

 REINFORCEMENT SHALL BE FULLY EMBEDDED IN GROUT AND SHALL BE MECHANICALLY SECURED TO INSURE PROPER LOCATION (DURO WALL OR EQUAL). AT 192 BAR DIAMETERS REINFORCEMENT SHALL NOT BE BEDDED IN MORTAR OR MORTAR JOINTS. PLACE THE VERTICAL STEEL PRIOR TO LAYING THE WALL. SEE STRUCTURAL NOTES AND DETAILS FOR SIZE, GRADE, LAPS, ETC.

CONSTRUCTION JOINTS: WHEN GROUTING IS STOPPED FOR A PERIOD OF ONE HOUR OR LONGER, FORM HORIZONTAL CONSTRUCTION JOINTS BY STOPPING THE GROUT POUR 2" MINIMUM BELOW THE UPPERMOST UNIT.

IF ANY SUCH BLOCKS ARE DISCOVERED IN ANY FINISHED WALL. THEY SHALL BE PROMPTLY REMOVED AND REPLACED WITH NEW BLOCKS TO THE APPROVAL OF THE ENGINEER. WALL CLEANING AND PROTECTION: REMOVE CONCRETE SCUM AND GROUT STAINS ON THE WALL IMMEDIATELY. AFTER THE WALL IS CONSTRUCTED. DO NOT SATURATE WITH WATER FOR CURING OR ANY

DEFECTIVE UNITS: DO NOT USE CHIPPED OR CRACKED BLOCKS.

OTHER PURPOSE. CHECK ALL JOINTS FOR TIGHTNESS AND WHERE CRACKS ARE VISIBLE, CHIP OUT THE MORTAR. TUCK POINT AND TOOL TO MATCH ADJACENT JOINTING. NO ELECTRICAL CONDUIT SHALL BE LOCATED IN THE SAME CELL AS TYPICAL VERTICAL OR JAMB BAR REINFORCING.

MAX. MASONRY LIFT HEIGHT SHALL NOT EXCEED 4 FT. SEE

SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.

DRILLED IN EXPANSION BOLTS AND ADHESIVE ANCHORS IN CONCRETE ALL DRILLED-IN EXPANSION ANCHORS SHALL BE HILTI KWIK BOLT III OR POWER'S BOLT (ICBO 1385, ICBO 1532) OR AN EQUAL APPROVED BY THE ENGINEER OF RECORD. SEE SPEC. SECTION

2. DRILLED-IN EXPANSION ANCHORS SHALL BE TENSION TESTED IN ACCORDANCE WITH THE FOLLOWING: a) 10%: WHERE USED FOR CONNECTION OF SILL PLATES.

b) 50% WHERE USED FOR NON-STRUCTURAL APPLICATIONS SUCH AS EQUIPMENT ANCHORAGE. d) 100% FOR THE ATTACHMENT OF ALL OTHER STRUCTURAL ATTACHMENTS THE TENSION TESTING OF THE EXPANSION ANCHORS SHALL BE DONE

IN THE PRESENCE OF THE PROJECT INSPECTOR AND A REPORT OF THE TEST RESULTS SHALL BE SUBMITTED TO THE ENFORCEMENT AGENCY. IF ANY ANCHORS FAIL THE TENSION-TESTING REQUIREMENTS, ADDITIONAL TESTING REQUIREMENTS ACCEPTABLE TO THE ENFORCEMENT AGENCY SHALL BE MADE. SEE SO.1 FOR FOR PULL TEST REQUIREMENTS.

CONSTRUCTION JOINTS

ADJACENT CONCRETE.

SPECIAL INSPECTION SPECIAL INSPECTION IN CONFORMANCE WITH SECTION 1701A OF THE 2001 CBC IS REQUIRED AND SHALL BE PROVIDED FOR THE FOLLOWING WORK, UNDER SUPERVISION OF AN OUTSIDE SPECIAL INSPECTION TESTING AGENCY EMPLOYED BY THE OWNER. SEE PROJECT SPECIFICATIONS FOR INDIVIDUAL REQUIREMENTS IN ADDITION TO THOSE LISTED BELOW:

a) STRUCTURAL CONCRETE WITH AN f'c GREATER THAN 2500psi b) ALL STRUCTURAL STEEL WELDING, EXCEPT WHERE DONE IN THE SHOP OF AN APPROVED FABRICATOR c) REINFORCING STEEL (WHERE F'C GREATER THEN 2500 PSI OR REINFORCEMENT IS WELDED)

d) WELDED REINFORCING BARS: CBC SECTION 1928A.12

e) USE OF STRUCTURAL EPOXIES f) USE OF A325 OR A325-S.C., A490-SC BOLTS q) BOLTS EMBEDDED IN CONCRETE OR MASONRY h) SOIL COMPACTION REQUIREMENTS ) TESTING, PREPARATION, AND PLACEMENT OF ALL CONCRETE MASONRY UNITS PER 2105A.7 ADHESIVE ANCHORS PER CBC SECTION 1925A.3.5

DRILLED-IN EXPANSION ANCHORS PER CBC SECTION 1925A.3.5 DRILLING AND INSTALLATION OF CIP PILES CEMENTITIOUS MATERIAL TESTS: CBC SECTION 1928A.1 REINFORCING BARS: CBC SECTION 1928A.2 BATCH PLANT INSPECTION: CBC SECTION 1928A.4 o) CONCRETE PLACING RECORDS: CBC SECTION 1928A.7

ALL CONSTRUCTION JOINTS SHALL BE CONSTRUCTED IN ACCORDANCE WITH CODE SECTION 1906A.4 AND THE TYPICAL CONSTRUCTION JOINT DETAILS SHOWN ON THE STRUCTURAL DRAWINGS. ALL SURFACES OF CONSTRUCTION JOINTS SHALL BE CLEANED TO REMOVE DUST, CHIPS, OR OTHER FOREIGN MATTER PRIOR TO PLACING THE

THE CONTRACTOR SHALL SUBMIT THE PROPOSED LOCATIONS OF CONSTRUCTION JOINTS TO THE ENGINEER FOR APPROVAL BY THE STRUCTURAL ENGINEER BEFORE STARTING CONSTRUCTION. (SEE SHEET SO.1 FOR CONTINUATION)

REINFORCEMENT DEVELOPMENT LENGTH & SPLICE TABLES (GR60 EXCEPT AS NOTED)

REINFORCEMENT DEVELOPMENT LENGTHS (LENGTH IN INCHES

#3 GR40 16 12	#4		ETE VFOR		AT	28 [	DAYS	SI
16	32	<b>#</b> 5					"40	
16	32	<u> </u>	#6	#7	#8	#a	1140	
		39			и -	T 3	#10	#1
12			47	69	78	88	100	110
	24	30	36	53	60	68	77	85
D (	201	ICR	ETE	· 1	f'c = AT		OO P	SI
		REII	VFOR	CEME	INT S	SIZE		,
#3 GR40	#4	<b>#</b> 5	#6	#7	#8	#9	#10	#1
16	29	36	43	63	72	81	102	125
13	22	28	33	48	55	62	78	96
D (	CON	ICR	ETE		f'c AT	= 40 28	DAYS	
		REI	VFOR	CEME	NT S	SIZE		
#3 GR40	#4	#5	#6	<b>#</b> 7	#8	#9	#10	#1
14	25	31	37	54	62	70	88	108
12	19	24	29	42	48	54	68	83
	#3 GR40 16 13 D ( #3 GR40 14	#3 #4 16 29 13 22 D CON #3 #4 GR40 #4 14 25	REIN #3 #4 #5 16 29 36 13 22 28  D CONCR REIN #3 #4 #5 GR40 #4 #5 14 25 31	REINFOR  #3 GR40 #4 #5 #6  16 29 36 43  13 22 28 33  ED CONCRETE  REINFOR  #3 GR40 #4 #5 #6  14 25 31 37	#3 #4 #5 #6 #7 16 29 36 43 63 13 22 28 33 48  D CONCRETE  REINFORCEME #3 #4 #5 #6 #7 14 25 31 37 54	REINFORCEMENT S  #3 #4 #5 #6 #7 #8  16 29 36 43 63 72  13 22 28 33 48 55  D CONCRETE f'c AT  REINFORCEMENT S  #3 #4 #5 #6 #7 #8  14 25 31 37 54 62	REINFORCEMENT SIZE  #3 #4 #5 #6 #7 #8 #9  16 29 36 43 63 72 81  13 22 28 33 48 55 62  D CONCRETE f'c = 40	REINFORCEMENT SIZE  #3 #4 #5 #6 #7 #8 #9 #10  16 29 36 43 63 72 81 102  13 22 28 33 48 55 62 78  D CONCRETE f'c = 4000 AT 28 DAYS  REINFORCEMENT SIZE  #3 #4 #5 #6 #7 #8 #9 #10  14 25 31 37 54 62 70 88

1. MIN. CENTER-TO-CENTER BAR SPACING > 3db 2. MIN. CONCRETE COVER > db

3. db= BAR DIAMETER

REINFORCED MASONRY f'm = 1500 PSI(CONCRETE BLOCK) REINFORCEMENT SIZE GR40 #4 #5 #6 #7 #8 #9 #10 #1 18 | 24 | 30 | 36 | 42 | 48 | 55 | 61 | 68

REINFORCEMENT LAP SPLICES (LENGTHS IN INCHES)

REINFORCED CONCRETE f'c = 2500 PSI AT 28 DAYS							SI		
REINF		REINFORCEMENT SIZE							
LOCATION	#3 GR40	#4	#5	#6	#7	#8	#9	#10	#11
TOP	21	42	51	62	90	102	115	130	143
OTHER	16	32	39	47	69	78	89	101	111
REINFORC	ED (	CON	ICR	ETE	•		300 28 [	DO P	SI
REINF			REIN	FORC	EME	NT S	IZE		
LOCATION	#3 GR40	#4	#5	#6	#7	#8	#9	#10	#11
TOP	21	38	47	56	82	94	106	132	162
OTHER	16	29	37	43	63	72	81	102	125
REINFORC	ED (	CON	ICR	ETE		f'c AT		DOO DAYS	
REINF			REIN	FORG	EME	NT S	IZE		
LOCATION	#3 GR40	#4	#5	#6	#7	#8	#9	#10	#11
TOP	18	33	41	49	71	81	91	114	140
OTHER	16	25	32	38	55	63	71	88	108

1. MIN. CENTER-TO-CENTER BAR SPACING > 3db 2. MIN. CONCRETE COVER > db 3. db= BAR DIAMETER

REINFORCED MASONRY f'm = 1500 PS							PSI .0CK)		
REINFORCEMENT SIZE				IZE					
	#3 GR40	#4	#5	#6	#7	#8	#9	#10	#11
	18	24	30	36	42	*	*	*	*
* SPLICED BY WELDING OR MECHANICAL CONNECTORS.									

WELDED WIRE FABRIC W5xW5@4x4 LAP SPLICE LENGTH IN TENSION = 12 IN.

TOP REINFORCING IS HORIZONTAL REINFORCEMENT THAT HAS MORE THAN TWELVE INCHES OF CONCRETE PLACED USE WELDED SPLICE OR MECHANICAL CONNECTOR IF THE Φ**●** BAR LAP SPLICE REINFORCEMENT DOES

NOT HAVE A MINIMUM SPACING

EVALUATION SERVICE, INC.

3dh+1/8 INCHES AND A MINIMUM COVER OF db+1/8 INCHES WELDED SPLICE (DIRECT BUTT SPLICES-FULL PENETRATION) #5 AND SMALLER SINGLE-BEVEL GROOVE WELD #6 AND LARGER DOUBLE-BEVEL GROOVE WELD NELDS SHALL HAVE THE ABILITY TO DEVELOP 125 PERCENT

3d\_+1/8\\_ SPLICE

OF THE YIELD STRENGTH FOR THE SPLICED REINFORCEMENT (75 KSI) MECHANICAL CONNECTORS MECHANICAL CONNECTORS SHALL BE TENSION—COMPRESSION TYPE WITH THE ABILITY TO DEVELOP 125 PERCENT OF THE YIELD STRENGTH FOR THE SPLICED REINFORCEMENT (75KSI) ALSO, MECHANICAL CONNECTORS SHALL HAVE AND BE INSTALLED PER AN EVALUATION REPORT FROM ICBO

MECHANICAL ANCHORAGE

GENERAL CONTRACTOR TO SUBMIT SHOP DRAWINGS AND ENGINEERING CALCULATIONS FOR THE ANCHORAGE, SUPPORT, AND SEISMIC BRACING OF MECHANICAL UNITS, DUCTS, EQUIPMENT, PIPING OR PLUMBING EQUIPMENT NOT ALEADY NOTED OR DETAILED ON EQUIPMENT SCHEDULES, OR ARCHITECTURAL ELECTRICAL, MECHANICAL OR STRUCTURAL DRAWINGS.

ALL SUBMITTALS SHALL BE SIGNED BY A STRUCTURAL ENGINEER

REGISTERED IN THE STATE OF CALIFORNIA AND APPROVED TO THE START OF FABRICATION. SEISMIC DESIGN FORCES SHALL ACT AT THE CENTER OF GRAVITY AND ASSUMED TO COME IN ANY DIRECTION PER 2001 C.B.C. SECTION 1632A. ADDITIONAL BUILDING/ SUPPORT FRAMING SHALL BE ADDED WHERE REQUIRED.

ABBREVIATIONS

**ABOVE** ANCHOR BOLTS ASPHALTIC CONCRETE ADDNL **ADDITIONAL** ABOVE FINISH FLOOR AGG AGGREGATE **ALTERNATE** ALUMINUM **APPROX APPROXIMATE** ARCH ARCHITECTURAL BLW BEVELED BEV BUILDING BLDG REAM BOC BOTTOM OF CONCRETE BOTTOM OF FOOTING BOT BRCG BRACING BEARING BRG PL BEARING PLATE BTW BETWEEN CC CENTER TO CENTER CIP CAST IN PLACE CONSTRUCTION JOINT CJ CTR CENTER CENTER LINE CLG CEILING CLR CLEAR CMU CONCRETE MASONRY UNIT COL COLUMN CONCRETE CONC

CONN CONNECTION CONT CONTINUOUS COMPLETE PENETRATION DOUBLE DEPR **DEPRESSED** DOUGLAS FIR DIAMETER DIAGONAL DIM DIMENSION DOWN

DWG DRAWING **EXISTING** EACH EACH FACE EF EBF ECCENTRICALLY BRACED FRAME EACH WAY EW EACH WAY EACH FACE EW EF **EXPANSION JOINT** ELEVATION EDGE OF SLAB EOS EACH SIDE EXP B EXPANSION BOLT **EXTERIOR** 

EN EDGE NAIL **FABRICATE** FLOOR DRAIN FD FINISH FLOOR FINISH GRADE FOUNDATION FACE OF CONCRETE FACE OF MASONRY FOOT/FEET FOOTING GALVANIZED

HEADED ANCHOR STUD HDR HORIZ HSA HORIZONTAL HSB HIGH STRENGTH BOLT INSIDE DIAMETER INTERIOR

LONG LEG HORIZONTA LONG LEG VERTICAL LAG SCREW LT WT LIGHT WEIGHT LONG

MAXIMUM

MACHINE BOL MASONRY CONTROL JOINT MECHANICAL MEZZANINE MISC MISCELLANEOUS METAL NEW NOT IN CONTRACT NUMBER

NTS NOT TO SCALE ON CENTER OD OUTSIDE DIAMETER OPG OPENING OPPOSITE HAND OPH PCC PRECAST CONCRETE

PERPENDICULAR

PARTIAL PENETRATION

PRESSURE PRESERVATIVE TREATER PRESSURE PRESERVATIVE TREATED PSF POUNDS PER SQUARE FOOT PSI POUNDS PER SQUARE INCH **RADIUS** REINFORCING REQD REQUIRED

SEE ARCHITECTURAL DRAWINGS SHRINKAGE JOINT SHORT LEG HORIZONTAL SLV SHORT LEG VERTICAL SHEET METAL SOG SLAB ON GRADE STAINLESS STEEL STAG STAGGER

> **STANDARD** STIFFENER STRUCTURAL **STRUC** SYM SYMMETRICAL THICK THK TOC TOP OF CONCRETE TOP OF FOOTING T.O.SLAB TOP OF SLAB

TOP OF STEEL TOP OF WALL TN TOE NAIL TUBE STEEL TYPICAL TOP AND BOTTOM

UNLESS OTHERWISE NOTED UNLESS NOTED OTHERWISE VERT. VERTICAL

WELDED STUD ANCHOR

WELDED WIRE FABRIC

Steinberg Group Architecture Planning Interiors 60 Pierce Avenue 3an Jose CA 95110 408.295.5446 tel 408.295.5928 fax

Fentress Bradburn ARCHITECTS LT Architecture • Interiors • Planning

421 Broadway (303) 722-5000 Denver, Colorado 80203 Fox-(303) 722-5080 Structural 726 Main St., Redwood City,

Engineering

Hensel Phelps Construction C



വ

ISSUED FOR: | DATE: DSA - INC #1 | 10.21.04

> 9 04/24/

DRAWING TITLE GENERAL NOTES DATE: 10.21.04

**REVIEW SET** 

SHEET NUMBER

PROJECT # 04043

2. ALL LIGHTGAGE METAL FRAMING CONSTRUCTION SHALL BE A ACCORDANCE WITH AISI "SPECIFICATIONS FOR DESIGN OF COLD FORMED STEEL STRUCTURAL MEMBER" LATEST EDITION.

3. ALL LIGHTGAGE METAL FRAMING SHALL CONFORM WITH THE FOLLOWING:

ASTM A653, GRADE 50 GALVANIZED STUDS: (Fy = 50,000 psi)12, 14 AND 16 GAUGE GALVANIZED STUDS: ASTM A653 GRADE 33 18 AND 20 GAUGE (Fy = 33,000 psi)GALVANIZED TOP TRACK: ASTM A653 GRADE 33 (Fv = 33,000 psi)16. 18. AND 20 GAUGE SLIPTRACK SYSTEMS OR INTERIOR VERTICAL PARTITIONS

GALVANIZED TRACK ASTM A653, GRADE 33, U.N.O.) (Fy = 33,000 psi)END CLOSURES, BRIDGING

AND ACCESSORIES

4. DOUBLE VERTICAL STUDS SHALL BE STITCH WELDED TOGETHER ON BOTH FLANGES WITH 1/16" GROOVE WELDS X 1" LONG AT 12" ON CENTER, U.N.O.

5. BOTTOM STUD TRACKS FOR INTERIOR PARTITIONS SHALL MATCH THE SIZE AND GAGE OF THE WALL STUDS AND SHALL HAVE 1.5" FLANGES (U.N.O.) TOP TRACKS AT INTERIOR PARTITION SHALL HAVE 1 3/8" FLANGES MATCH THE SIZE AND GAGE OF TYPICAL STUDS BUT SHALL BE 16 GA, MIN, AND SHALL BE MANUFACTURED BY SLIP TRACK SYSTEMS OR EQUAL.

6. MINIMUM SECTION PROPERTIES FOR STEEL STUDS AT INTERIOR PARTITIONS AND THOSE STUDS REFERENCED ON ARCHITECTURAL DRAWING SHALL BE AS

	EFFECTIVE ,	EFFECTIVE	EFFECTIVE
	$S_{xx} = IN^3$	$I_{xx} =1N^4$	$A = IN^2$
35/6" STUDS: 35/6" X 20 GA 35/6" X 18 GA 35/6" X 16 GA 35/6" X 14 GA	0.292 0.389 0.468 0.584	0.551 0.710 0.873 1.069	0.262 0.340 0.422 0.524
35%" X 20 GA TRACK 35%" X 18 GA TRACK 35%" X 16 GA TRACK 35%" X 14 GA TRACK	0.174 0.245 0.332 0.453	0.384 0.531 0.705 0.921	0.212 0.276 0.346 0.436
4" STUDS: 4" X 20 GA 4" X 18 GA 4" X 16 GA 4" X 20 GA TRACK 4" X 18 GA TRACK 4" X 16 GA TRACK	0.290 0.383 0.457 0.201 0.282 0.381	0.603 0.776 0.953 0.484 0.666 0.882	0.249 0.323 0.401 0.225 0.293 0.367
6" STUDS: 6" X 20 GA 6" X 18 GA 6" X 16 GA 6" X 20 GA TRACK 6" X 18 GA TRACK 6" X 16 GA TRACK 6" X 16 GA TRACK	0.510 0.670 0.809 0.331 0.519 0.655 0.680	1.582 2.042 2.518 1.291 1.766 2.229 2.383	0.318 0.413 0.514 0.294 0.383 0.480 0.509
8" STUDS: 8" X 16 GA STUDS 8" X 14 GA STUDS 8" X 16 GA TRACK 8" X 16 GA DL TRACK	1.218 1.512 0.967 0.969	4.873 6.049 4.559 4.847	0.612 0.766 0.594 0.622
10" STUDS: 10" X 1 5/8" X 16 GA STUDS 10" X 16 GA TRACK 10" X 16 GA DL TRACK	1.716 1.436 1.756	9.958 7.994 8.878	0.783 0.702 0.731
12" STUDS: 12" x 1 5/8" X 16 GA STUDS 12" X 3" X 14 GA STUDS 12" X 16 GA TRACK 12" X 16 GA DL TRACK	4.000 1.655	14.982 28.415 12.862 14.133	0.896 1.387 0.816 0.844
14" STUDS: 14" X 1 5/8" X 14 GA STUDS 14" X 3" X 14 GA STUDS 14" X 14 GA TRACK 14" X 14 GA DL TRACK	4.632 3.036	28.304 40.613 24.690 26.454	1.263 1.530 1.167 1.203

THESE VALUES ARE TAKEN FROM THE SSMA CATALONG, ICBO#4943P & THE DIETRICH CATALOG ICBO #4784. ALL PROPERTIES FOR TRACKS REFLECT 1 3/8" OR 1 1/4" FLANGE, AND ALL PROPERTIES FOR DEEP LEG TRACKS REFLECT 1 1/2" FLANGE.

7. ALL SHEET METAL SCREWS SHALL PROTRUDE 1/4" THROUGH METAL FRAMING. 8. AS A MINIMUM ANCHOR TRACK TO CONCRETE WITH HILTI 0.145" DIAMETER X-DNI (ICBO #2388) LOW VELOCITY POWDER DRIVEN INSERTS @ 16" o.c. OR APPROVED EQUAL. THE INSERTS SHALL HAVE A MINIMUM 1 1/2" EMBEDMENT INTO THE CONCRETE AND SHALL BE LOCATED A MINIMUM 3" FROM ANY

CONCRETE EDGE. THE INSERTS SHALL BE PLACED ADJACENT TO EACH WALL

- STUD AT A MAXIMUM DISTANCE OF 3". POWDER DRIVEN ANCHORS SHALL NOT BE USED IN CONCRETE CURBS.
- 10. CONTRACTOR SHALL COMPLY WITH ALL OF THE MANUFACTURER'S INSTALLATION SPECIFICATIONS AND RECOMMENDATIONS. ALL METAL STUDS SHALL HAVE STIFFENED FLANGES. SEE DRAWINGS FOR SPECIFIC DETAILS ON CONNECTIONS, BRACING, BRIDGING, ETC. CONTRACTOR SHALL PROVIDE ALL ACCESSORIES INCLUDING. BUT NOT LIMITED TO, TRACKS, CLIPS, AND OTHER ACCESSORIES REQUIRED FOR A COMPLETE AND PROPER INSTALLATIONS, AND AS RECOMMENDED BY THE MANUFACTURER FOR THE STEEL MEMBERS USED.
- 11. ALL METAL STUDS TO BE MANUFACTURED BY MEMBERS OF THE STEEL STUD MANUFACTURER'S ASSOCIATION, SSMA (ICBO #4943P), U.N.O.
- 12. SEE ARCH PLAN FOR SPECIAL METAL STUD FRAMING WHERE INDICATED. 13. FOR FASTENERS INSTALLED IN CONCRETE, MINIMUM SPACING BETWEEN FASTENERS
- IS 4" o.c. AND MINIMUM EDGE DISTANCE IS 3", TYP. U.N.O. 14. FOR FASTENERS INSTALLED IN STEEL (3/16" MIN. THICKNESS), MINIMUM SPACING BETWEEN FASTENERS IS 1 1/2" o.c. AND MINIMUM EDGE DISTANCE IS 1/2".
- FASTENERS SHALL BE DRIVEN TO A PENETRATION WHERE THE SHANK PIERCES THE STEEL BASE, UNLESS AS NOTED ON PLAN, TYP. U.N.O. 15. FOR SHEET METAL SCREWS INSTALLED IN LIGHT GAUGE METAL FRAMING, MINIMUM SPACING BETWEEN FASTENERS IS 1 1/2" o.c. AND MINIMUM EDGE DISTANCE IS
- 16. AS MINIMUM PROVIDE (2) #10 SMS AT EACH LIGHT GAUGE METAL MEMBER CONNECTION, U.N.O.

3/4" TYP. U.N.O.

N. STRUCTURAL OBSERVATION

STRUCTURAL OBSERVATION WILL BE PERFORMED BY THE STRUCTURAL ENGINEER OF RECORD OR DESIGNEE IN ACCORDANCE WITH SECTION 1702A OF THE CBC CODE.

2. STRUCTURAL OBSERVATION IS THE VISUAL OBSERVAION OF THE ELEMENTS AND CONNECTIONS OF THE STRUCTURAL SYSTEM AT SIGNIFICANT CONSTRUCTION STAGES AND THE COMPLETED STRUCTURAL FOR GENERAL CONFORMANCE TO THE APPROVED PLANS AND SPECIFICATIONS. STRUCTURAL OBSERVATION DOES NOT WAIVE THE RESPONSIBILITY FOR THE INSPECTIONS REQUIRED OF THE BUILDING INSPECTOR OR THE DEPUTY INSPECTOR.

3. THE CONTRACTOR SHALL COORDINATE AND CALL FOR A PRE-CONSTRUCTION MEETING BETWEEN THE ENGINEER OR ARCHITECT RESPONSIBLE FOR THE STRUCTURAL DESIGN, STRUCTURAL OBSERVER, CONTRACTOR, AFFECTED SUBCONTRACTORS, BUILDING AND DEPUTY INSPECTORS. THE PURPOSE OF THE MEETING SHALL BE TO IDENTIFY THE MAJOR STRUCTURAL ELEMENTS AND CONNECTIONS THAT AFFECT THE VERTICAL AND LATERAL LOAD SYSTEMS OF THE STRUCTURE AND TO REVIEW SCHEDULING OF THE REQUIRED OBSERVATIONS.

4. THE STRUCTURAL OBSERVER SHALL PERFORM SITE VISITS AT THOSE STEPS IN THE PROGRESS OF THE WORK THAT ALLOW FOR CORRECTION OF DEFICIENCIES WITHOUT SUBSTANTIAL EFFORT OR UNCOVERING OF THE WORK INVOLVED. AT A MINIMUM, THE FOLLOWING SIGNIFICANT CONSTRUCTION STAGES REQUIRE A SITE VISIT.

CONSTRUCTION STAGES	ELEMENTS/CONNECTIONS TO BE OBSERVED
A) FOUNDATIONS	REINF / DOWELS / ANCHORS
B) CONCRETE WALLS	REINF / DOWELS / SPLICES
C) STEEL ERECTION	COLUMNS / BEAMS /BRACES /CONNECTION
D) FLOOR DECKING	REINF / STUDS / WELDING

- . FOR STRUCTURAL ANCHORAGE OF MECHANICAL EQUIPMENT SEE SHEETS MECHANICAL DRAWINGS.
- 2. FOR STRUCTURAL ANCHORAGE OF ELECTRICAL EQUIPMENT SEE SHEETS ELECTRICAL DRAWINGS.
- 3. FOR STRUCTURAL ANCHOR OF PLUMBING EQUIPMENT SEE PLUMBING DRAWINGS.
- 4. FOR STRUCTURAL ANCHORAGE OF LABORATORY/SCIENTIFIC
- SEE ARCHITECTURAL DRAWINGS. 5. NO EQUIPMENT SHALL BE INSTALLED WITHOUT APPROVED SUPPORT AND ANCHORAGE DETAILS EXCEPT ITEMS IN THE
- CATEGORIES LISTED BELOW (SEE CBC PART 1, SECTION 7-125(c): A. EQUIPMENT WEIGHING LESS THAN 400 POUNDS THAT IS SUPPORTED ON A FLOOR OR ROOF.
- B. FURNITURE.
- C. TEMPORARY OR MOVEABLE EQUIPMENT.
- D. EQUIPMENT WEIGHING LESS THAN 20 POUNDS AND SUSPENDED ON OR HUNG FROM A WALL.
- E. EQUIPMENT WEIGHING LESS THAN 20 POUNDS AND SUSPENDED FROM A ROOF OR FLOOR.
- SOME ITEMS IN THE ABOVE CATEGORIES MUST BE ANCHORED. THEIR ANCHORAGE IS SUBJECT TO FIELD REVIEW EVEN IF THEIR ANCHORAGE DETAILS ARE NOT SHOWN IN THE APPROVED DOCUMENTS.
- \*ATTACHMENTS OF EQUIPMENT WEIGHING LESS THAN 400# AND SUPPORTED DIRECTLY ON THE FLOOR OR ROOF STRUCTÜRE. FURNITURE OR TEMPORARY OR MOVABLE EQUIPMENT WEIGHING LESS THAN 20# THAT IS SUPPORTED BY VIBRATION ISOLATION DEVICES SUSPENDED FROM THE ROOF, WALL, OR FLOOR NEED NOT BE DETAILED ON THE PLANS. (CBC TITLE 24 PART 2 SECTION 1630A.1) HOWEVER, SUCH EQUIPMENT MUST BE SUPPORTED AND ANCHORÉD TO RESIST THE FORCES PRESCRIBED BY SECTION 1630A.2 AND THE ANCHORAGE SHALL BE APPROVED BY THE STRUCTURAL ENGINEER OF RECORD AS PART OF FIELD REVIEW/INSPECTIONS. THE INSPECTOR OF RECORD SHALL ASSURE THAT THE ABOVE REQUIREMENTS ARE ENFORCED.
- ALL PIPES, DUCTS, AND CONDUITS SHALL BE SUPPORTED AND BRACED FOR ALL FORCES IN ACCORDANCE WITH 2001 CBC CHAPTER 1632A. GENERAL CONTRACTOR SHALL SUBMIT FINAL SUPPORT AND BRACING CONSTRUCTION DRAWINGS SHALL BE SUBMITTED FOR REVIEW AND APPROVAL OF THE STRUCTURAL ENGINEER OF RECORD FOR GENERAL CONFORMANCE WITH THE ORIGINAL DESIGN INTENT.
- FOR ALL VIBRATION ISOLATORS AND THEIR ANCHORAGES, CONTRACTOR/ MANUFACTURER SHALL PROVIDE CALCULATIONS, DETAIL, AND/ OR TEST DATA TO SUBSTANTIATE THE ISOLATOR'S CAPACITY FOR VERTICAL AND LATERAL LOADS.
- 9. SPACING AND DETAILS OF THE SUPPORT AND BRACING OF FIRE SPRINKLER PIPING SHALL COMPLY WITH THE 1999 EDITION OF NFPA 13 AND CHAPTER 35 OF THE CALIFORNIA AMENDMENTS. PROVIDE STRUCTURAL ENGINEER WITH ANCHORAGE DETAILS AND CALCULATIONS FOR THE CONNECTION OF SWAY BRACING TO THE STRUCTURE. DESIGN LOADS FOR THE ANCHORAGE MAY BE COMPUTED PER TABLE 4-14,4,3,5,3 OF NFPA 13 OR BY A RATIONAL ANALYSIS OF THE PIPING SYSTEM, WHERE APPLICABLE, DETAILS FOR THE SUPPORT AND BRACING MAY BE REFERRED TO PRE-APPROVED ANCHORAGE SYSTEM. ALL SHOP DRAWINGS OF THE SPRINKLER SYSTEM SHALL BE SUBMITTED TO THE STRUCTURAL ENGINEER FOR REVIEW AND APPROVAL PRIOR TO INSTALLATION. THE ALLOWABLE VALUES FOR ANCHORS IN TABLE 4-6.4.3.5.4 MAY NOT COMPLY WITH THE REQUIREMENTS OF THE CODE. REFER TO THE ADOPTED CBC FOR ALLOWABLE LOADS ON THE SPECIFIC FASTENER TYPE. CONTRACTOR SHALL BE RESPONSIBLE FOR MEETING THESE REQUIREMENTS. THE ALLOWABLE VALUES FOR EXPANSION ANCHORS SHALL BE DETERMINED IN ACCORDANCE WITH IR 19-1.

- 1. ANCHOR DIAMETER REFERS TO THE THREAD SIZE OF THE WEDGE
- 2. APPLY PROOF TEST LOADS TO WEDGE ANCHORS WITHOUT REMOVING THE NUT IF POSSIBLE. IF NOT, REMOVE NUT AND INSTALL A THREADED COUPLER TO THE SAME TIGHTNESS OF THE ORIGINAL NUT USING A TORQUE WRENCH AND APPLY LOAD.
- 3. REACTION LOADS FROM TEST FIXTURES MAY BE APPLIED CLOSE TO THE ANCHOR BEING TESTED, PROVIDED THE ANCHOR IS NOT RESTRAINED FROM WITHDRAWING BY THE FIXTURE(S).
- 4. TEST EQUIPMENT IS TO BE CALIBRATED BY AN APPROVED TESTING LABORATORY IN ACCORDANCE WITH STANDARD RECOGNIZED
- 5. THE FOLLOWING CRITERIA APPLY FOR THE ACCEPTANCE OF INSTALLED HYDRAULIC RAM METHOD: THE ANCHOR SHOULD HAVE NO OBSERVABLE MOVEMENT AT THE APPLICABLE TEST LOAD. FOR WEDGE AND SLEEVE TYPE ANCHORS, A PRACTICAL WAY TO DETERMINE OBSERVABLE MOVEMENT IS THAT THE WASHER UNDER THE NUT
- BECOMES LOOSE. 6. TESTING MUST OCCUR 24 HOURS MINIMUM AFTER INSTALLATION OF

THE SUBJECT ANCHORS.

- 7. WHEN INSTALLING DRILLED-IN ANCHORS AND /OR POWDER DRIVEN PINS IN EXISTING NON-PRESTRESSED REINFORCED CONCRETE, USE CARE AND CAUTION TO AVOID CUTTING OR DAMAGING THE EXISTING REINFORCING BARS.
- 8. THESE TENSION VALUES ARE ONLY APPLICABLE WHEN THE ANCHORS ARE INSTALLED WITH SPECIAL INSPECTION AS SET FORTH IN SECTION 306 OF THE CODE.
- 9. THE TABULATED VALUES ARE FOR ANCHORS INSTALLED A MINIMUM OF 12 ANCHOR DIAMETERS ON CENTER AND A MINIMUM EDGE DISTANCE OF 10 ANCHOR DIAMETERS, (U.N.O).
- 10. THE TABULATED VALUES FOR LIGHT WEIGHT CONCRETE ARE THE ANCHORS INSTALLED IN LIGHTWEIGHT EXPANDED SHALE AGGREGATE CONCRETE HAVING THE COMPRESSIVE STRENGTH AT THE TIME OF INSTALLATION. CONCRETE AGGREGATE MUST COMPLY WITH U.B.C. STANDARD NO. 19-3
- 11. "\*" ANCHORS INSTALLED AT THIS EMBEDMENT DEPTH SHALL NOT BE USED TO RESIST SHEAR DUE TO WIND OR SEISMIC FORCES PER ICBO REPORT #1385.

EXPANSION TYPE CONCRETE WEDGE ANCHOR DESIGN & TEST VALUES. HILTI-KWIK BOLT-III CARBON STEEL WEDGE ANCHORS (ICBO REPORT <u>#1385)</u>

TABLE 1A

3,000 PSI NORMAL WEIGHT CONCRETE

ANCHOR	DEPTH (PC		N VALUES	TENSION	
DIA			JNDS)	TEST	
(INCHES)	(INCHES)	ŚHEAR	TENSION	(POUNDS)	
1/4	1 1/8*	359	270	540	
	2	359	535	1070	
	3	359	571	1,142	
3/8	1 5/8	850	677	1,354	
	2 1/2	1,004	1139	2,278	
	3 1/2	1,004	1248	2,496	
1/2	2 1/4	1,396	1,027	2,054	
	3 1/2	1,493	1,638	3,276	
	4 3/4	1,465	1,765	3,530	
5/8	2 3/4	2,062	1,518	3,036	
	4	2,659	2,244	4,488	
	5 1/2	2,659	2,770	5,540	
3/4	3 1/4	3,059	1,784	3,568	
	4 3/4	3,761	3,165	6,330	
	6 1/2	3,761	4,295	8,590	
1	4 1/2	5,300	2,920	5,840	
	6	6,900	4,248	8,496	
	9	6,900	5,640	11,280	

THESE VALUES REFLECT 80% OF ICBO REPORT VALUES FOR SHEAR. THESE VALUES ASSUME SPECIAL INSPECTION AND REFLECT 80% OF ICBO REPORT VALUES FOR TENSION.

TABLE 1B

4,000 PSI NORMAL WEIGHT CONCRETE

ANCHOR DIA	DEPTH (POUNDS)		TENSION TEST	
(INCHES)	(INCHES)	SHEAR	TENSION	(POUNDS)
1/4	1 1/8*	359	319	638
	2	359	596	1,192
	3	359	613	1,226
3/8	1 5/8	850	810	1,620
	2 1/2	1,004	1335	2,670
	3 1/2	1,004	1335	2,670
1/2	2 1/4	1,396	1,215	2,430
	3 1/2	1,493	1,828	3,656
	4 3/4	1,465	1,931	3,862
5/8	2 3/4	2,062	1,623	3,246
	4	2,659	2,512	5,024
	5 1/2	2,659	3,076	6,152
3/4	3 1/4	3,059	2,008	4,016
	4 3/4	3,761	3,924	7,848
	6 1/2	3,761	5,252	10,504
1	4 1/2	5,300	3,500	7,000
	6	6,900	5,300	10,600
	9	6,900	6,444	12,888


THESE VALUES REFLECT 80% OF ICBO REPORT VALUES FOR SHEAR. THESE VALUES ASSUME SPECIAL INSPECTION AND REFLECT 80% OF ICBO REPORT VALUES FOR TENSION.

TABLE 1C

3 1/4" LIGHTWEIGHT CONCRETE OVER 1 1/2" METAL DECK (F'c=3000 PSI)

ANCHOR DIA	FROM BOTTOM OF (POUNDS)		TENSION TEST	
(INCHES)	FLUTE (INCHES)	SHEAR	TENSION	(POUNDS)
1/4	2"	460	495	600
3/8	2 1/2"	650	826	1652
1/2	3 1/2"	1011	1280	2560

THE ABOVE VALUES WERE CACULATED USING IR 19-1. & ICBO ER-1385 EFFECTIVE EMBEDMENT IS CONSIDERED HEIGHT OF ANCHOR ABOVE METAL DECK + 1/3 DECK HEIGHT. THESE VALUES REFLECT 80% OF ICBO REPORT VALUES FOR SHEAR. THESE VALUES ASSUME SPECIAL INSPECTION AND REFLECT 80% OF ICBO REPORT VALUES FOR TENSION.



THE ABOVE VALUES WERE CACULATED USING IR 19-1. & ICBO ER-1372 EFFECTIVE EMBEDMENT IS CONSIDERED HEIGHT OF ANCHOR ABOVE METAL DECK + 1/3 DECK HEIGHT. THESE VALUES REFLECT 80% OF ICBO REPORT VALUES FOR SHEAR. THESE VALUES ASSUME SPECIAL INSPECTION AND REFLECT 80% OF ICBO REPORT VALUES FOR TENSION.

Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in any way. If an item in this document is altered by followed by his signature and the date of such alteration, and a specific description of the alteration.

TABLE 1E

HILTI KWIK BOLT-III EXPANSION ANCHORS IN GROUTED MASONRY (ICBO REPORT #1385

ANCHOR DIA	EMBEDMENT DEPTH	MIN. DISTANCE FROM EDGE OF WALL (INCHES)	DESIGN (POUI	VALUES NDS)	TENSION TEST
(INCHES)	(INCHES)	WALL (INCILS)	SHEAR	TENSION	(POUNDS)
	1 1/8	4	304	121	242
1/4	1 1/6	12	304	121	242
1/4	•	4	342	432	864
	2	12	342	432	864
	- /-	4	589	257	514
7/0	1 5/8	12	751	273	546
3/8	2 1/2	4	764	626	1252
		12	1054	626	1252
1 (0 0 1 (4	0.4/4	4	664	502	1004
1/2	2 1/4	12	1171	533	1066
	7 1 /0	4	840	724	1448
	3 1/2	12	1853	724	1448
		4	710	651	1302
5 /0	2 3/4	12	1732	692	1384
5/8	_	4	743	994	1988
	4	12	2123	1035	2070
	7 4 /4	4	627	829	1658
7/4	3 1/4	12	2508	829	1658
3/4		4	657	1316	2632
	4 3/4	12	2627	1368	2736

THESE VALUES REFLECT 80% OF ICBO REPORT VALUES FOR SHEAR. THESE VALUES ASSUME SPECIAL INSPECTION AND REFLECT 80% OF ICBO REPORT VALUES FOR TENSION.

TABLE 1F

POWER-BOLT CARBON STEEL EXPANSION SLEEVE ANCHORS (ICBO REPORT #1532) 3,000 PSI LIGHT WEIGHT CONCRETE

ANCHOR DIA	EMBEDMENT DEPTH FROM BOTTOM OF		DESIGN VALUES (POUNDS)		
(INCHES)	FLUTE (INCHES)	SHEAR	TENSION	(POUNDS)	
1/4	1 1/4"	472	184	368	
3/8	2"	548	318	736	
1/2	2 1/2"	880	400	800	
5/8	2 3/4"	888	400	800	

THE ABOVE VALUES WERE CACULATED USING IR 19-1. & ICBO ER-1532 EFFECTIVE EMBEDMENT IS CONSIDERED HEIGHT OF ANCHOR ABOVE METAL DECK + 1/3 DECK HEIGHT. THESE VALUES REFLECT 80% OF ICBO REPORT VALUES FOR SHEAR. THESE VALUES ASSUME SPECIAL INSPECTION AND REFLECT 80% OF ICBO REPORT VALUES FOR TENSION.

TABLE 1G

POWER-STUD CARBON STEEL EXPANSION WEDGE ANCHOR (ICBO REPORT # 1532) 3,000 PSI LIGHT WEIGHT CONCRETE

ANCHOR DIA	EMBEDMENT DEPTH FROM BOTTOM OF		N VALUES UNDS)	TENSION TEST
(INCHES)	FLUTE (INCHES)	SHEAR	TENSION	(POUNDS)
1/4	1 1/8"	368	176	352
3/8	1 5/8"	560	304	608
3/6	3"	768	896	1792
1/2	2 1/4"	956	640	1280
1/2	3"	1192	912	1824
5 /Q	2 3/4"	956	640	1280
5/8	3 1/2"	1432	1108	2216

THE ABOVE VALUES WERE CACULATED USING IR 19-1. & ICBO ER-1532 EFFECTIVE EMBEDMENT IS CONSIDERED HEIGHT OF ANCHOR ABOVE METAL DECK + 1/3 DECK HEIGHT. THESE VALUES REFLECT 80% OF ICBO REPORT VALUES FOR SHEAR. THESE VALUES ASSUME SPECIAL INSPECTION AND REFLECT 80% OF ICBO REPORT VALUES FOR TENSION.

ADHESIVE TYPE ANCHORS: HAS THREADED RODS WITH HILTI HY150 ADHESIVE (ICBO REPORT #5193)

TABLE 2A

3,000 PSI NORMAL WEIGHT CONCRETE

ANCHOR DIA	DIA DEPTH		DESIGN VALUES (POUNDS)		
(INCHES)	(INCHES)	SHEAR	TENSION	(POUNDS)	
3/8	1 3/4	494	744	1,488	
	3 1/2	1,496	1,720	3,440	
	5 1/4	3,052	2,037	4,075	
1/2	2 1/8	720	1,048	2,096	
	4 1/4	2,336	2,097	4,195	
	6 3/8	4,477	3,600	7,200	
5/8	2 1/2	984	1,353	2,707	
	5	3,200	3,616	7,232	
	7 1/2	6,373	5,344	10,688	
3/4	3 3/8	1,700	2,358	4,716	
	6 5/8	5,504	5,078	10,156	
	10	10,980	8,120	16,240	
7/8	3 3/4	2,241	2,980	5,960	
	7 1/2	7,049	7,040	14,080	
	11 1/4	14,205	11,240	22,480	
1	4 1/8	2,696	3,116	6,232	
	8 1/4	8,764	7,488	14,976	
	12 3/8	17,112	13,150	26,300	

TABLE 2B

4,000 PSI NORMAL WEIGHT CONCRETE


				Constitution in the second section of the second section of the second section is a second section of the second section of the second section is a second section of the se
ANCHOR	DEPTH	DESIGI	TENSION	
DIA		(POL	TEST	
(INCHES)	(INCHES)	SHEAR	TENSION	(POUNDS)
3/8	1 3/4	580	948	1,896
	3 1/2	1,752	2,032	4,064
	5 1/4	3,576	2,100	4,200
1/2	2 1/8	844	1,180	2,360
	4 1/4	2,736	2,952	5,904
	6 3/8	5,248	3,972	7,944
5/8	2 1/2	1,152	1,492	2,984
	5	3,748	3,936	7,872
	7 1/2	7,468	6,182	12,364
3/4	3 3/8	1,992	2,944	5,888
	6 5/8	6,448	6,664	13,328
	10	12,864	9,104	18,208
7/8	3 3/4	2,628	3,648	7,296
	7 1/2	8,260	8,200	16,400
	11 1/4	16,644	12,484	24,968
1	4 1/8	3,160	3,648	7,296
	8 1/4	10,268	8,728	17,456
	12 3/8	20,048	14,644	29,288

Architecture Planning Interior

60 Pierce Avenue San Jose CA 95110 408.295.5446 tel 408.295.5928 fax

Fentress Bradburn ARCHITECTS LTI Architecture • Interiors • Planning

421 Broadway (303) 722-5000 Denver, Colorado 80203 Fax-(303) 722-5080 Engineering





ISSUED FOR: DATE: DSA - INC #1 | 10.21.04


8


DRAWING TITLE GENERAL NOTES


DATE: 10.21.04 PROJECT # 04043 SHEET NUMBER

















Hensel Phelps Construction Co. Andrew Brown Prolog WebSite	With the second	Timica   waste
estion  Date Required; It is a securify that detail 10 on sheet S1.6 of Increment One drawings is to occur on only one side of the beam. If no		The winds of the second of the
ase provide locations.  ggestion re is more clarification on Detail 10/S1.6:	O. SOL WIZNES	T. VIES X 3 TO
<i>!</i>	3. 180	W100.33 / 18 / 18 / 18 / 18 / 18 / 18 / 18 /
At one side of all building perimeter beams  /	)) wroken	WINGS WINGS
At one side of all openings of stairs & elevators	igon i i i i i i i i i i i i i i i i i i i	WILLIAM OF THE PROPERTY OF THE
At interior locations on any one side of frame beams with not more than 10'-0" o.c. to laterally brace the top and ge of frame beams. As shown on plan drawings, one lateral bracing beam will be always provided at center of ce-frame beam where braces intersect. As shown on plan drawing SB2.03 gridline 6, one lateral bracing beam	bottom	
ce-frame beam where braces intersect.  As shown on plan drawing SB2.03 gridline 6, one lateral bracing beam bays provided on any one side, at center of special moment frame beam and at 3'-0" away from special moment frame beam and at 3'-0" away from special moment frame beam and at 3'-0" away from special moment frame beam and at 3'-0" away from special moment frame.	frame	The state of the s
as, Crosby Group		M16×36
swer	swered.	
Dan Deakon Lescure	Rice Card	
Hensel Phelps Construction Co. Pale Skyline College Building 6 & 7A	E 3	(F) 1.4
Request For Information		The state of the s
Project # 5004030 Jobsite Info. Hensel Phelps Construction Co. 3500 College Drive Tel: 650-355-5578 San Bruno, CA 94066 Fax: 650-355-7428  RFI#: 0140 Date Created: 11/3/2005		W16631 (21)1 - (8)
Answered By  Ron Saiki,  The Steinberg Group  Authored By  Laine Heikel, Hensel Phelps Construction Co.	E STONA E	W2AY68 (188) EQ SEE S11.0 FOR STAIR WILL STRUCTURAL (TY FRAMING
60 Pierce Avenue 3500 College Drive San Jose, CA 95110 San Bruno, CA 94066  Co-Respondent Subcontractor RF, Number	Too The second of the second o	26 (25) 24 (25) W100 (26)
HPCC 0093  Subject  Bolts at Moment Connection of Gravity Columns		11
Location Discipline CSI Division Structural Metals	E House E	W 10x15
Drawling/Spec Revision Date Detail/Section Question	The mone of	W21x44 (10) Ho
Reference Increment No. 1, sheet S1.5; detail 1; sheet S1.6 detail 2; and sheet S1.7 detail 1  Detail 1 of sheet S1.5 of Moment Connection at Gravity Columns refers to detail 2 of sheet S1.6 for the type of bolts to be used in fine situation, calling out A325-N bolts. However, sheet S1.7 detail 1 specifies a different type of bolt, A490-SC, to be used at	29.8. MIENZI 1101 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	8 - 1C (57.1) 16 (57.1) 17 (77.1) 17 (77.1)
Please confirm moment connections at gravity columns require the A325-N bolts called out on sheet S1.6 detail 2, and not thos consultant Comments	WBx13 (4)	W10x12 TYP. BETWEEN LINE  1.4 &(3)
325-SC bolts per det. 2/S1.6 are required at moment connections per det.1/S1.5 except that if the moment connection olumn happens to be a collector location then det. 2/S1.7 applies. Collector locations are marked with a dark dot on ceams shown on framing plans/// Tejas, Crosby Group.  nswer:  Date Answered: 11/3/2003.	Muoxi	wiens 2
ee comments by Tejas, Crosby Group. Saiki CC Company Name Contact Name Copies Notes CIS inc. Kurt Dodge Prolog WebSite	16'-63/4	(1.4) (Cpuite 2
The Crosby Group Tejas Goshalia Prolog WebSite Hensel Phelps Construction Co. Andrew Brown Prolog WebSite	NA STATE OF THE ST	1516 8106
	C. Seems	
formance!         Printed on: 11/7/2005         P_HPCC_B3038_PM72_5004030         Page 1	The state of the s	
	100.8. A SOLUTION OF THE PROPERTY OF THE PROPE	
BAM Decker Lescure		W16x31 (24)
Hensel Phelos	105.8 1 105.8	E. S. MINNE (6) / E.
Construction Co.  Skyline College Building 6 & 7A Request For Information Detailed, Each RFI  Jobsite Info. Tel: 650-355-5578 Fax: 650-355-7428  Skyline College Building 6 & 7A Request For Information Detailed, Each RFI  Hensel Phelps Construction Co. Fex: 650-355-7428		
REI#: 0140.1 Date Created: 11/7/2005 Date Required: 11/14/2005	B.3	The state of the s
Aunored By Swar.	The state of the s	The state of the s
Cabeditactor RFI Number	CO C	
Subject  Bolts at Moment Connection of Gravity Columns	The state of the s	
-ocation Discipline		The state of the s
Structural Metals  Prawing/Spec Royleign		
Structural Metals  Drawing/Spec Revision Date Detail/Section  Ruestion  eference Increment No. 1, sheet S1.5, detail 1; sheet S1.6 detail 2; sheet S1.7 detail 1; and RFi 140		Thomas of the state of the stat
Structural Metals  Drawing/Spec Revision Date Detail/Section  Revision Date Detail/Section  Revision Date Detail/Section  Detail 1; sheet S1.5 detail 1; sheet S1.6 detail 2; sheet S1.7 detail 1; and RFi 140  Detail 1 and RFi 140		Wind to the state of the state
Structural Metals  Drawing/Spec Revision Date Detail/Section  Ruestion  eference Increment No. 1, sheet S1.5, detail 1; sheet S1.6 detail 2; sheet S1.7 detail 1; and RFi 140		Williams of the state of the st
Structural Metals  Drawing/Spec Revision Date Detail/Section		11.02.10 12 12 12 12 12 12 12 12 12 12 12 12 12
Structural Metals  Drawing/Spec Revision Date Detail/Section  Resettion  Reference Increment No. 1, sheet S1.5, detail 1; sheet S1.6 detail 2; sheet S1.7 detail 1; and RFi 140  Drift further clarification the cantilevered beams on building 6 long the perimeter at the mentioned areas are to have a moment punnection per detail 1 on S1.5 and using A325 bolts.  Antilevered beams along gridline "G" between 1.4 and 3 antilevered beams along gridline "G" between "A" and "D" peams in the "Feature Wall" along gridline "E" between 9-11" off-set of 1 and 1 on 2nd and roof level.  Description of the perimeter of 1 and 1 on 2nd and roof level.  Description of 1 and 1 on 2nd and roof level.  Description of 1 and 2 on 2nd and roof level.  Description of 1 and 2 on 2nd and roof level.  Description of 1 and 2 on 2nd and roof level.  Description of 1 and 2 on 2nd and roof level.  Description of 1 and 2 on 2nd and roof level.  Description of 1 and 2 on 2nd and roof level.  Description of 1 and 2 on 2nd and roof level.  Description of 2 on 3 on		Wights to the state of the stat
Structural Metals  Drawing/Spec Revision Date Detail/Section  Resettion  Reference Increment No. 1, sheet S1.5, detail 1; sheet S1.6 detail 2; sheet S1.7 detail 1; and RFi 140  or further clarification the cantilevered beams on building 6 long the perimeter at the mentioned areas are to have a moment onnection per detail 1 on S1.5 and using A325 bolts.  antillevered beams along gridline "G" between 1.4 and 3 antilevered beams along gridline 6 between "A" and "D" sams in the "Feature Wall" along gridline "E" between 9-11" off-set of 1 and 1 on 2nd and roof level.  Donsultant Comments  onfirmed Tejas, Crosby Group.  Iswer  e comments from Tejas, Crosby Group.  Saiki  Company Name  Contact Name  Copies  Notes  The Crosby Group  Tejas Goshalia  Prolog WebSite	E THE THE PARTY OF	HIDATO TO THE SE STATE OF STAT
Structural Metals  Drawing/Spec Revision Date Detail/Section  Resettion  Reference Increment No. 1, sheet S1.5, detail 1; sheet S1.6 detail 2; sheet S1.7 detail 1; and RFi 140  or further clarification the cantilevered beams on building 6 long the perimeter at the mentioned areas are to have a moment onnection per detail 1 on S1.5 and using A325 bolts.  antillevered beams along gridline "G" between 1.4 and 3 antilevered beams along gridline 6 between "A" and "D" sams in the "Feature Wall" along gridline "E" between 9-11" off-set of 1 and 1 on 2nd and roof level.  Donsultant Comments  onfirmed Tejas, Crosby Group.  Iswer  e comments from Tejas, Crosby Group.  Saiki  Company Name  Contact Name  Copies  Notes  The Crosby Group  Tejas Goshalia  Prolog WebSite	E THE THE PARTY OF	Winds of the state
Structural Metals  Drawing/Spec Revision Date Detail/Section  Resettion  Reference Increment No. 1, sheet S1.5, detail 1; sheet S1.6 detail 2; sheet S1.7 detail 1; and RFi 140  or further clarification the cantilevered beams on building 6 long the perimeter at the mentioned areas are to have a moment onnection per detail 1 on S1.5 and using A325 bolts.  antillevered beams along gridline "G" between 1.4 and 3 antilevered beams along gridline 6 between "A" and "D" sams in the "Feature Wall" along gridline "E" between 9-11" off-set of 1 and 1 on 2nd and roof level.  Donsultant Comments  onfirmed Tejas, Crosby Group.  Iswer  e comments from Tejas, Crosby Group.  Saiki  Company Name  Contact Name  Copies  Notes  The Crosby Group  Tejas Goshalia  Prolog WebSite	E THE THE PARTY OF	Winds of the state
Structural  Structural  Metals  Prawing/Spec Revision Date Detail/Section  Structural  Metals  Date Detail/Section  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail 1 on S1.5 and using A325 bolts.  Date Detail/Section  Date Detail/Section  Date Detail/Section  Date Detail/Section	E THE THE PARTY OF	Winds of the state


, ·


¥











7/\$8.1.1

3. WHERE COLUMN IS PART OF A BRACED FRAME OR MOMENT FRAME, USE BASE PLATE FOR BRACED FRAME. SEE \$10.11, U.N.O.

All Growthy columns to have embedoment of 1-2" anchor bolts

1. ADD DOUBLER PLATES AS NOTED ONLY IF COLUMN IS PART OF A MOMENT FRAME (SEE SHEET \$1.7)

2. BASE PLATE REFERENCED APPLIES UNLESS AN ALTERNATE DETAIL IS SPECIFICALLY NOTED ON PLANS

Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in any way. If an item in this document is altered by followed by his signature and the date of such alteration, and a specific description of the alteration.

(11) W18x50

PER BASE R DET.

\* PFT coal

4' 113/0"

KHI 33 see back street

NOT USED

CF-47 4'-6"X7'-0" 2'-0" #5@8"OC EW #4@16"OC E.W. CF-510 5'-0"x10'-0" 3'-0" #5@6"OC EW #5@6"OC EW

尼在 00%

CF818 8'-0"x18'-6" 2'-6" #5@6"OC EW #5@6"OC EW SEE 18/S8.1.3

CF812 8'-0"x13'=0" 2'-6" #5@6"OC EW #5@6"OC EW SEE 19/S8.1.3

6-#5

3-#5

5<del>-</del>#5

5-#5

5-#5

7-#6

8-#6

| TIES #3@8" OC

TIES #4@8" OC

TIES #4@8" OC

TIES #4@8" 00

TIES #4@8" 00

TIES #4@8" 00

12-#6 TIES #4@8" OC

GB-2 2'-0" 1'-6" 3-#5

GB-6 6'-0" 2'-0" 12-#6

5-#5

5-#5

5-#5

7-#6

8-#6

SPLICE GRADE BEAM REINF WITHIN MIDDLE 1/3 OF

SPAN BETWEEN EDGES OF ADJACENT SPREAD FOOTINGS

GB-2.5 2'-6" 2'-0"

GB-2.8 2'-8" 2'-0"

GB-3 3'-0" 2'-0"

GB-3.5 3'-6" 2'-0"

GB-4 4'-0" 2'-0"

POHILIPERS 29,302,4091,941,124,124,128,

60 Pierce Avenue

San Jose CA 95110 408.295.5446 tel 408.295.5928 fax

Fentress

Bradburn

Structurel Engineering

ARCHITECTS LTD Architecture • Interiors • Planning 421 Broadway (303) 722~5000 Denver, Colorado 80203 Fax-(303) 722-5080

726 Mein St., Redwood City, CA 94063 tal. (650) 367–6100 fax. (650) 367–6189


Hensel Phelps Construction C

**KEY PLAN** 

BUILDING A FIRST FLOOR PLAN DATE: 10.21.04 PROJECT # 04043 SHEET NUMBER SA2.01

DRAWING TITLE

ISSUED FOR: DATE: DSA - INC #1 10.21.04




Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in this document is altered by followed by his signature and the date of such alteration, and a specific description of the alteration.

12 322

	Hensel Constru	Phelp uction	s Co.					/le		0								•			
Skyline	Styline College									<u> 26</u>				4 dob	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					,,,,,	
							Da	<u>.</u> Sk	/ 27/	ונג	A			700 9	Ö						
RFI Fac installa	033						70	m sego	01 100	y be requ	ured or	n or the	tare								
						12 1	3: 1#	≨ 1 <sub>1</sub> 5	·16 ·	1.7 1	- B	9 2I	<b>)</b> 21-	- 22	- 23	24	25 2	B - 2	F -25	2 <del>9</del> -	-36
0	ranger op 19		. p i						-1	Ĭ				[		1				. ,	· •
<u> </u>						1		}-	, .ì	4		?		·	. }		<del>-</del>		·	<del>{-</del> -	
		<u>.</u>	<del>-</del>			ļ. —					<u> </u>	<del>-</del>			!		- <u>}</u>	}!	• 🕆	:	. 1
		· j j	الم الم	- ‡		i		}-	n of the s			- 5	= \$	/ !! 9				إ	-cx - sp	s	
5		<del></del>		ب. أُجمع . أُجمع		· · · ·		<u>-</u>	<u>.</u>	<del></del>				<del></del> †	<u>→</u>	is sele				1	- ' ;
b	·				٦	<u>;</u> .	2	- }	1	17	§		1	7	1	V	77			ATE	/Sub61
7	-1-1-			1	X		(		1			-	,	7		14			j	1	
8		+	1 729	1	À-	5					_		,							;	;
9			The state of	16-	-	1				i			į		. ].		1				إس
10	-11		17		7				1		A LINE SEC				luv	e moter con				ا مانيسس	***************************************
	-17	T		-	-	-								j			<u> </u>	L -			;
12		_ حدد حرب الـ ا	1		1			i i		1	<u> </u>	$\setminus$		į		J		į			
13		T			1			100		·	<u>.</u>	, <b>.</b>	//6.	1	3	. 2	N.	; 		100 =	~ e4
ta							1			1-	ļ., .					1_	<u>.                                    </u>	ļ		·	
is 1											1						ļ	ļ.,	; i		:
7					1.	1	ECONOMIC S	1			<u>:</u>				ļ.	ļ.	ļ	ļ			
18.						1					<u>[</u>			, \$0,000		n spra	-	1 -	! }	-	
19		. In process of			<u>.</u>	ļ	<u>.</u>		 }	4.		t Serverien				- 4 -				. ;	-
20				_n			ļ	ļ	· - <del> </del>	<u> </u>			ļ		<del>-</del> -	<del>-</del>		ļ	·		/3 
21		J	أسيان	. إلىه با		ļ.,	ļ.,	<u>.</u>				ļ			<u>-</u> i		. <del>†</del> -	- -			
22		1-	4_	4	ران	t to	ት (	<u>)</u>	10	. ک	Ϋ́	1	16	۲.,	SHA	FI	ļ	ļ.,			
23				De	. سېچىن	المتاب	وجع	129			ļ	<u> </u>		;			<del>-</del> -	<u> </u>	!	-	
24	<u>ļ. į. į.</u>	_  .				-	ļ	ļ	-	. <del></del>		<u> </u>					4		-	}	
25	1	<u> </u>				<u>.</u>	1		إ			T	ļ		•		; ·-	ļ			
26.	<u>                                   </u>		-;;			ļ.,		ļ	<u>Ļ</u>			ì		,,,,,			i	-	<u> </u>	1	<u>'</u>
27				_ ‡		<u> </u>		<u>}_</u> ;	‡		ļ	, 			}	- 1	•		! 	-	
28							-	} . !	٠. إ٠		ļ.	; !	ļ., .		ij	<del>.</del>		į	-		-
29							÷	<u>-</u>			·	+		-			4		ļ		
30			1		1		1	1			de	£	ļ 				., ‡		<u> </u>		

Performancel



Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in any way. If an item in this document is altered by followed by his signature and the date of such alteration, and a specific description of the alteration.


Steinberg Group

60 Pierce Avenue San Jose CA 95110 408.295.5446 tel 408.295.5928 fax

Bradburn ARCHITECTS LTD. Architecture + Interiors + Planning 421 Broadway (303) 722-5000 Denver, Colorado 80203 Fax-(303) 722-5080

Structural
Engineering
728 Main St.,
Redwood City,
CA 94003
to 4 (650) 367-8100
fox. (650) 367-8189


Hensel Phelps Construction C



ISSUED FOR: DATE: DSA - INC #1 10.21.04

DRAWING TITLE BUILDING A -THIRD

FLOOR FRAMING PLAN DATE: 10.21.04 PROJECT # 04043 SHEET NUMBER




Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in any way. If an item in this document is altered, the alteration of the law for any person, unless acting under the direction of a licensed architect, to alter an item in this document is altered, the alternation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in this document is altered, the alternation.

PCO#11: PFIC 29, 32, 40, 91, 94.1, 124, 126, 128, 129, 132, 151, 154, 166, 160, 162.1, 165, 167, 169, 170, 170, 177, 1, 179, 186, 190 AND 191.

STRUCTURAL STEEL WODIFICATIONS DUE TO MINOR ERRORS.

### **ROOF FRAMING NOTES**

- 1. FOR GENERAL NOTES AND TYPICAL DETAILS, SEE SHEETS S0.0, S0.1, S1.1, S1.2, S1.3, S1.4, S1.5, S1.6, S1.7
- 2. "C" INDICATES BEAM CAMBER.
- 3. FOR METAL DECK PROPERTIES, ATTACHMENTS AND DETAILS SEE SHEET \$1.3.
- 4. VERIFY ALL DIMENSIONS, ELEVATIONS, COLUMN GRIDS AND INTERIOR AND EXTERIOR GRADES WITH ARCHITECTURAL DRAWINGS PRIOR TO CONSTRUCTION
- 5. SEE DRAWINGS OTHER THAN STRUCTURAL FOR FLOOR AND WALL FINISHES, SLOPES, DEPRESSIONS, PENETRATIONS, CURBS AND EXACT NUMBERS AND LOCATIONS OF EQUIPMENT SUPPORTED ON THE ROOF AND/OR SUSPENDED BELOW THE ROOF, SEE MECHANICAL DRAWINGS FOR ROOF MOUNTED EQUIPMENT SUPPORTS.
- 6. SEE ARCHITECTURAL DRAWINGS FOR LOCATIONS OF ALL WALLS.
- 7. S.A.D. FOR LOCATION AND EXTENT OF TAPERED INSULATION.
- 8. SEE 5/S1.4 & 7/S1.4 FOR SUPPORT OF ALL AIR HANDLING UNITS.
- 9. DENOTES LT WT. TOPPING OVER GALVANIZED METAL DECK (3 SPAN MIN. EXCEPT WHERE NOTED). PROVIDE MINIMUM WELDED WIRE REINFORCEMENT 4X4-W5 X W5 THROUGHOUT. SEE PLAN FOR THICKNESS. SEE SO.O FOR WWF LAP SPLICE LENGTHS.



DENOTES TOP OF CONCRETE TOPPING SLAB.

DENOTES TOP OF STEEL ELEVATION.


INDICATES VERTICAL SEISMIC SEPARATION JOINT THROUGH ROOFS, AND SECOND FLOOR SLABS WHERE OCCURS. SEE ARCHITECTURAL DRAWINGS FOR WIDTH AND EXTENT.

- 12. UNLESS OTHERWISE SHOWN, USE C8X11.5 TO SUPPORT ALL FLOOR MOUNTED OR SUSPENDED MECHANICAL EQUIPMENT GREATER THAN 200#, OR DECK OPENING GREATER THAN 24" PERPENDICULAR TO METAL DECK DIRECTION. SEE DETAIL 1/S1.4
- 13. SEE DETAIL 12/S1.4 FOR SUPPORT AT SMALL FLOOR & ROOF OPENINGS.
- 14. INDICATES TYPICAL MECHANICAL/PLUMBING ROOF PENETRATION.
  SEE 1 & 12/S1.4 FOR SUPPORT.
- 15. ALL STEEL BEAMS SHOWN BEAR ON THE CENTER OF STEEL OR CONCRETE OR CMU COLUMNS (WHERE APPLICABLE) AND SHALL BE EQUALLY SPACED BETWEEN BEARING POINTS & GRIDLINÉS AS SHOWN U.N.O.
- 16. ALL MECHANICAL UNITS AND AND PENETRATIONS SHOWN ARE APPROXIMATE. GENERAL CONTRACTOR TO COORDINATE WITH UNIT MANUFACTURER, ARCHITECTURAL, AND MECHANICAL DRAWINGS FOR ACTUAL SIZE AND LOCATION.

17. — INDICATES AREA OPEN TO BELOW.

- 18. [28] INDICATES THE NUMBER OF 3/4" H.A.S., SEE 14/S1.3. (SPACE EQUALLY IN PORTION OF BEAM W/ CONC. DECK). 19. \_\_\_\_\_\_ INDICATES CMU BEARING OR NON-BEARING WALL BELOW.
- 20. INDICATES BRACE FRAME HORIZONTAL MEMBER. SEE FOUNDATION PLANS FOR BRACED FRAME TYPE.
- 21. \_\_\_\_\_ INDICATES DIAGONAL BRACE UP FROM FOUNDATION OR 2ND FLOOR.
- INDICATES DIAGONAL BRACE DOWN FROM ROOF.
- INDICATES STEEL WELDED MOMENT CONNECTION WITH REDUCED BEAM SECTION PER SHEET S1.7, SEE ALSO S1.5 AND S1.6 FOR CANTILEVER BEAM AND COLUMN CONNECTION TO PERPENDICULAR BEAMS AND COLUMNS AT NON-MOMENT FRAME COLUMN BAYS.
- 24. STEEL BEAMS WHICH HAVE SPECIFIED OR INCIDENTAL SHOP CAMBER SHALL BE PLACED WITH CAMBER UP IN ALL LOCATIONS U.O.N.
- 25. INDICATES BEAM TO COLUMN OR BEAM TO BEAM COLLECTOR CONNECTION. SEE SHEET S1.6.
- 26. \* INDICATES SLIP CRITICAL CONNECTION. TIGHTEN PER TABLE J3.7 AISC MANUAL OF STEEL CONSTRUCTION (LATEST EDITION)
- INDICATES TYPICAL ROOF DRAIN. SEE ARCH/MECH/PLUMBING DRAWINGS AND 12/S1.4 FOR DECK SUPPORT. Okay to run conduit in

metal deck



DATE: 10.21.04 PROJECT # 04043 SHEET NUMBER

Group

60 Pierce Avenue San Jose CA 95110 408.295.5446 tel 408.295.5928 fax

Fentress

ARCHITECTS LTD

Architecture • Interiors • Planning

42! Broadway (303) 722-5000 Denver, Colorado 80203 Fax-(303) 722-5080

Structural
Engineering
726 Moin St.,
Redwood City.
CA 940633
tal. (650) 367-8100
fax. (650) 367-8189

Hensel Phelps Construction C

ISSUED FOR: DATE:

DSA - INC #1 10.21.04


6.7 C.E.S

Architecture Planning Interior

Bradburn

**REVIEW SET** 


DRAWING TITLE BUILDING A - ROOF



-5-ADDITIONAL #4
BARS CONT. @
BRACE FRAME BAYS

CMU WHERE
OCCURS

4-ADDITIONAL #5
BARS CONT @
BRACE FRAME BAYS



Reference Sheet SB2.01 and Sketch A

1) In building 6 at the waste receptacle the exterior wall for the stairs the rebar located on grid line HH.1 in sketch A was installed 8" to far north.

2) At the same area on grid line 11.2 the rebar for the 10" wall was stopped north of door opening and does not run to the edge of the building.

Please provide the depth and spacing the replacement bar holes need to be drilled.

Consultant Comments.


Rebar-dowels should match wall vertical reinforcement size and spacing ... Provide 6" (min.) rebar-dowel embeddment in concrete wall footing with COVERT CIA-7000 gel epoxy adhesive (ICC evaluation report ESR-1072 or equal) ... drill holes for dowels should not damage existing footing reinforcement ... III ... Tejas, Crosby Group.


Answer


Date Answered: 11/3/2005


See comments by Tejas, Crosby Group. PCO for DSA approval will be required.


R. Saiki














ga.

				10-24-74-74-74-74-74-74-74-74-74-74-74-74-74	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,							В	RA	CEI	) F	RA	\M [	(			EC	T   (	NC		SCI	<u> </u>					
BLDG.	BRACE	100	ATION		BRA	CING	MEN	/BER	-									С	ONNE	CTIOI	NS						<del></del>				
DLDG.	BAY		AHON	1ST	FLOC	)R	21	ND FLO	OR	COI	INECTION	I AT FIF	RST FLOC	)R	CONI	NECTION	BELOW	/ 2ND F	LOOR	CC	NNECT	ION AT	SECON	ID FLO	D FLOOR		CONNECTION BE		BELO	OW ROOF	REMARKS
	TYPE	GRID	BETWEEN	SIZE	WEL	D "A" LENGTH	SIZE		LD "A"	PLATE WE	LD "B"	WELD	C" R	EFERENCE DETAIL	PLATE WE	LD "B"	WELD	C" F	REFERENCE DETAIL	PLATE "P"	WELD "	B" NGTH S	WELD '	'C" F	REFERENCI DETAIL	PLATE	WEL	.D "B" LENGTH	WEI	_D_"C" REFERENCE LENGTH DETAIL	
TUDENT UNION	BF-2A	14	H & JJ	HSS5x5x1/2			_			5/8 5/1		A CONTRACTOR OF THE CONTRACTOR			3/4 3/4						_		_	-	<u> </u>	-	-	_	_		
	BF-2A	Н	12 &:14	HSS6x6x1/2	1/2	12		-		3/4 3/8	18	5/8	22	***	1 5/8	64	-		****	_	_		_		_		-		-		
	BF-2A	HH	11 & 11.5	HSS6x6x1/2	1/2	12	THE PARTY OF THE P		-	3/4 5/1	5 18	1/2	30	_	3/4 3/4	52	_			-			and the second s		_		-	_	_		
	BF-1B	10.2	A.3 & B.3		1/2	12	HSS5x5x3	3/8 3/8	12	3/4 5/1	5 18	1/2	30		3/4 3/4	56	_	_	_	1/2 1	/4	18 1	/2	18	_	3/4	1/2	48	-		
	BF-18	А	7 & 8		1/2	12	HSS5x5x3	3/8 3/8	12	3/4 5/1	18	1/2	30		3/4 3/4	62	-	_		1/2	3/8	25 5	/16	12	•••	3/4	1/2	48	_		
	BF-1A	6	A & B		1/2	12			-	3/4 5/1	18	1/2	30		3/4 3/4	56		-				_		-				-	-		SMRF ABOVE 2ND FLOOR
	BF-1A	6	C & D		1/2	12			_	3/4 5/1	5 18	1/2	30		3/4 3/4	56			-		40 Principles 4 Variables 4 Va	_		-	_		-		_		SMRF ABOVE 2ND FLOOR
	BF-1B	B.3	9 & 10.2	HSS6x6x5/8	1/2	15	HSS5x5x1	/2 1/2	12	3/4 1/2	21	5/8	24		1 5/8	88	-	_	_	1/2 1	/2	24 5	/16	10	<del></del>	3/4	5/8	58	_		
	BF-1B	1.7	F & G	HSS6x6x5/8	1/2	15	HSS6x6x	3/8 1/2	12	3/4 5/1	5 21	5/8	32		3/4 3/4	62	-	_	_	1/2 5	8/8	17 5	/16	17	· <del></del>	3/4	5/8	48	_		
	BF-1B	К	11.5 & 12	HSS6x6x1/2	1/2	12	HSS5x5x5	/16 3/8	12	3/4 5/1	18	1/2	30	<b></b>	1 5/8	62	-		_	1/2	3/8	25 5	/16	12		3/4	1/2	48			
	BF-1B	L.3	11.5 & 12	HSS6x6x5/8	1/2	15	HSS5x5x1	/2 1/2	12	3/4 5/1	3 21	5/8	32		1 5/8	70	-	_	<del></del>	1/2	/2	24 5	/16	10		3/4	5/8	56	_		NUMBER OF THE PROPERTY OF THE
	BF-18	11.5	K & L.3	HSS6x6x3/8	1/2	12	HSS5x5x5	/16 3/8	12	5/8 5/1	3 18	1/2	21		3/4 1/2	74	_	-	<del>-</del>	1/2	3/8	25 5	/16	12	****	3/4	3/8	67	_		
	BF-2A	12	K & L.3		1/2	12	**************************************		-	5/8 5/1	3 18	1/2	21	_	3/4 1/2	74	_	-		_	-	_	University				-		_		
	BF-1B	13	K &c M	<b> </b>	1/2	12	HSS5x5x5	/16 3/8	12	5/8 5/1	3 17	1/2	28		3/4 5/8	60				1/2	3/8	25 5	/16	12	****	3/4	5/8	_	-		
	BF-1C	G1	3 & 3.2	HSS5x5x1/2	1/2	12	HSS4x4x	1/4 3/8	12	3/4 5/1	3 20	3/8	35	<u> </u>	3/4 -		1/4	37		1/2 1	/4	18 1	/2	18	<del>_</del>	5/8	-	_	_		
	BF-1E	G1	3.2 & 4	HSS6x6x5/8	1/2	15	HSS5x5x3	3/8 3/8	12	3/4 5/1	3 21	5/8	32	_	3/4 3/4	62	_	_		1/2	3/8	62	_	-	<del>_</del>	3/4	5/8	48	-		
	BF-1C	G1	4 & 13	HSS5x5x1/2	1/2	12	HSS4x4x1	1/4 3/8	12	3/4 5/1	3 20	3/8	35	Maria.	3/4 -	-	1/4	37		1/2 1	/4	18   1	/2	18		5/8		Generalis de la Companya de la Compa			
		I	1	T					1			<del> </del>				1	- <del> </del>	T	· · · · · · · · · · · · · · · · · · ·				<del></del>			-			T T		·
SU/DINING AREA	BF-2C	15	J & L	HSS6x6x3/8	1/2	. 12				3/4 5/1	3 20	3/8	35					_		_	-	-	- Anthre and the anthre anthre and the anthre anthre anthre and the anthre and the anthre anthre and the anthre	-		3/4	5/16	20	3/8	32 -	
	BF-2B	15	N & P	HSS6x6x3/8	1/2	12	_			3/4 5/1	3 20	3/8	35				_   _	_		-	_	-		_ ]	*****	3/4	3/4	38	-	-   -	
	BF-2A	17	L.3 & NN	HSS6x6x3/8	1/2	12	_		_	3/4 5/1	3 22	5/16	44				-	-		-	-	-		- Company		3/4	1/2	42	-		
	BF-2A	17	K & M	HSS6x6x3/8	1/2	12	-	_	_	3/4 5/1	3 22	5/16	44				_	-		_	_	-	-	-		3/4	1/2	42	-		
	BF-2A	J	15 & 16	HSS6x6x1/2	1/2	12	_			3/4 5/1	3 20	1/2	32			_	_			_	-		_		<del>-</del>	3/4	1/2	48			
	BF-2A	Р	15 & 16	HSS6x6x1/2	1/2	12	_			3/4 5/1	3 20	1/2	32	_ :		-	-			-	-		_	_	_	3/4	1/2	48			

### BRACED FRAME CONNECTION SCHEDULE

BLDG.	BRACE		ΑΤΙΩΝ	В	RACIN	NG M	/EMBER	2												CONN	ECTI(	SNC																				
DLDG.	BAY		AIION	2ND F	LOOR		3RD FLO	OR	PENT	HOUSE		CONN	IECTION .	T SECOND	FLOOR	C	ONNECT	ION BELO	W 3RD	FLOOR		CONNECTI	ION AT	THIRD FLO	OOR	СО	NNECTIO	N BELOW F	ROOF		COI	NNECTION A	AT ROO	F	Cr	ONNECT	ON BELOV	N PENTH	DUSE		REMA	RKS
	TYPE	GRID	BETWEEN	SIZE S	WELD "A"	" STH S	WE SIZE SIZE	ELD "A"	SIZE	WELD "	A" PL	ATE WEI	LD "B"	WELD "C"	REFEREI	NCE PLATI	SIZE L	B" V	WELD "C"	REFERENCE TH DETAIL	DE PLATE	WELD "E	3" SIGTH SIZ	WELD "C"	REFERENC DETAIL	PLATE V	WELD "B"	WELD "(	REFEREN	NCE PLATE	E WELD SIZE L	"B" WI ENGTH SIZE	/ELD "C"	REFERENCE TH DETAIL	CE PLATE	SIZE I	"B" V ENGTH SIZ	E LENGTI	REFERENCI DETAIL	Ε		
ENCE ANNEX	BF-1B	D	3 &4	HSS6x6x5/8 1			A COLUMN TO A COLU							5/8 24				70 –						16 12			į		ļ		_			_		_	1	_				
	BF-1B	D	4 & 5	HSS6x6x5/8 1	/2 15	5 HSS	55x5x5/16 3/8	12	_	_	- 3/	<sup>'</sup> 4 1/2	21	5/8 24		3/4	5/8	70 –		_	1/2	3/8 2	25 5/	16 12	_	1/2 3/	8 50				-	_   _	-   -			-					alah Sirikka di Sand-Abelian di Kababa Silah di Kababa Alba di Kababa da Abelia da Abelia da Abelia da Abelia	
	BF-1B	A	3 & 4	HSS6x6x1/2 1	/2 12	2 HSS	65x5x5/16 3/8	12	<del></del>	_	- 3,	4 3/8	18	5/8 22	_	3/4	5/8	70 –		-	1/2	3/8 2	25 5/	16 12	_	1/2 3/	8 50						_					-				
	BF-1B	А	4 & 5	HSS6x6x1/2 1	/2 12	2 HSS	65x5x5/16 3/8	12	_	_	- 3/	<sup>′</sup> 4 3/8	18	5/8 22		3/4	5/8	70 –			1/2	3/8 2	25 5/	16 12	_	1/2 3/	8 50			_				_								
	BF-1B	1	C & D	HSS6x6x1/2 1	/2 12	2 HSS	S5x5x5/16 3/8	12	_	_	- 3/	4 5/16	18	1/2 30	_	3/4	5/8	88 -			1/2	1/4 1	18 1,	/2 18	-	1/2 3/	8 64		-	-			-									
	BF-1B	3	A & B	HSS6x6x1/2 1	/2 12	2 HSS	65x5x5/16 3/8	12	_	_	- 3,	4 5/16	18	1/2 30	_	3/4	5/8	88 -	-		1/2	1/4 1	18 1,	/2 18	_	1/2 3/	8 64		_			_   -	-			_						
·	BF-1B	5	A & B	HSS6x6x5/8 1	/2 15	5 HSS	55x5x5/16 3/8	12		_	- 3,	<b>/</b> 4   5/16	21	5/8 32	_	3/4	5/8	88 -			1/2	1/4 1	18 1,	/2 18	_	1/2 3/	8 64		_				_			-						
	BF-1B	7	C & D	HSS6x6x5/8 1	/2 15	5 HSS	S5x5x5/16 3/8	12			- 3,	<b>′</b> 4 5/16	21	5/8 32	-	3/4	5/8	88 -			1/2	1/4 1	18 1,	/2 18		1/2 3/	8 64							_				_			4444477777777	<b>**********</b>
															**************************************		V					-																			**************************************	
	BF-3A	3	C &c D	-				_	HSS4x4x1/4	3/8	12	-   -			-		_			-   -			_   _		_				-	1/2	1/4	18 3/8	8 27		1/2	3/8	37 –		_			
	BF-3A	5	C & D	-	-	_		-	HSS4x4x1/4	3/8	12	- [		-	_				-			_	_   _	·   -	_				-	1/2	1/4	18 3/8	8 27		1/2	3/8	37 –				***************************************	
	BF-3A	BTWN C & D	4 & 5	-				_	HSS4x4x1/4	3/8	12 -	_					_	_   -	_			-			-					1/2	3/8	25 5/1	16 12		1/2	3/8	48	_	-			
	BF-1D	В	3 & 4	-	-	-		_	HSS4x4x1/4	3/8	12 -		_			-	-		•	<u> </u>	_		_	-   -			-   -		-	1/2	3/8	25 5/1	16 12		1/2	3/8	50 –	-				
																				and the state of t					Acceptable descriptions			The state of the s				displayed and the second description of the	CONTRACTOR OF THE PARTY OF THE				Anna de la companya d		de la constante de la constant			

NOTE: 1. LENGTH OF WELD LEG, WELD "B" AND WELD "C", ARE THE MINIMUM REQUIRED LENGTHS SET PER UNIFORM FORCE METHOD.

2. FOR BRACE FRAME TYPE CONFIGURATION SEE SHEET S5.1.

3. WELD SIZE, LENGTH & PLATE THICKNESS ARE IN INCHES.

4. PROVIDE BRACE OVERSLOT REINFORCMENT PLATE AS SHOWN IN DET. 9/S10.11 (TYP.).

1 BRACE FRAME CONNECTION SCHEDULE


NO SCALE

The
Steinberg
Group
Architecture Planning Interiors
60 Pierce Avenue
San Jose CA 95110
408.295.5446 tel
408.295.5928 fax

Fentress
Bradburn
ARCHITECTS LTD.
Architecture • Interiors • Planning
421 Broadway
Denver, Colorado 80203 Fax-(303) 722-5080

Structural Engineering 726 Mein St., Redwood City, CA 94063 tel. (650) 367-8 group group

(LE) Hensel Phelp



INE COLLEGE

JUNITY SERVICES CENTER AND SCIENCE ANNEX BUILDING

STUDENT SUPF

SSUED FOR: DA

DSA - INC #1 10.21.

IDENTIFICATION STAMP

IV. OF THE STATE ARCHITECT

ICE OF REGULATION SERVICES

APPL # 01-106658

APPL # 01-106658

BRACE FRAME
SCHEDULE


DATE: 10.21.04


PROJECT # 04043


DRAWING TITLE

PROJECT # 04043
SHEET NUMBER

S6.1









| 150.100 | 1- 67|2-100 | Date | 12/81/2-05 | Shc | | By: TVG | Ck: rojet gray come constant EFE # 111

#### CORNER OF GRIDLINE S/A 4 5/6 :

This calculation is to check shear teamsper prom STEEL FRAME COLUMNS & THEIR CONCRETE PILASTERS TO THE CONCRETE SHEAR WALLS ALONG LINE 5 ( A OR live 5 \$ 0 (as applicable) may have capacity to Accommonts the pesical loads.

DESIGN LOADS: ( REF "NC + 1 STRUCT CALL SHOOT & ACT) column on the A/S : Hope & 129

Bass = 127.5"

# NOTE : IT IS CHECKED THAT HET UPLIFT IS ON PER CALC. SHEAT ACES & ACES.

- # ARAVITY LOADS FOR SELF-INT & LIVE LOADS CAN BE CARRIED BY SPEEL COL. To FOUNDATIONS ... OK.
- & PEANE LATERAL LOADS ARE CARRIED BY CONT. WALLS VIA. CHEAR TRANSPER B. . COL. OK.
- + WE OUT HELD TO CHECK TRANSPER OF STEEL COL. optiff tokes to come, wasts.



	higher survives couvers	Job No: 1- 475 - 105
**	Description:	Date: 12 10: 12-05 Stt.
		By: TV6x Ck: 2/2.

HAN DEHAND FOR SHEAR FRICTION DUS to Uplift 多种现象 = 49月 - 孔玉.


Mare than Y4" amplitude Roughwegg 0.9 × 110.2 ... 2.2 × 113.2 2 160 k.


AVAILABLE STEAR FRICTION CAPACITY : + th = 0.85 × Ay × Jx /L.


- = 0.95 x 2x 0.2x 60 x 1.0 x [12 x 12/6]
- = 367.2 × > 150 = 25


- 1. WE ACKNOWLED AT THE RESARS WERE BENT 2 TIMES AS APPROVED BY DEA.
- 2. FIELD COMPTIEN SHOWS HORE THAN "4" AMPLITUDE FOR ROTATIONED SUPPACE.
- THERE IS UNACCOUNTER AVAILABLE RESERVED FOR IN PARTICIPALITY IN PILASTER CONC. FROM PARTICIPALITY by steel col. Studs & VERT. & Ametioned & Developed the court foothers
- 4. CALCULATED CAPACITY > 2× DEMAND ... (367 > 1115)

BASES AN ABOVE TEMS 1, 2,5,4 ... WE ALLOW COENER 44 PERAR DOWNL , SHOWN "IN DET 13/ SE-1-2 HE OMITTED FRAM CONSTRUCTION.









\*\*\* \* \* \* \* \* \* \* \*

Question


Reference Increment No. 1 drawings sheet SB2.02 and SB2.03 as well as sheets S8.3.1 detail 8 and S8.3.2 details 14 and 13.


Also reference attached sketch.

The flat beams for the feature wall on gridline E are to be connected using a 1/2" thick stiffner plate to the beam's flanges. Although these pieces are correct per drawings and details, the offset between the centerlines has been found to be unacceptable to weld properly as specified. (See sketch) This situation occurs in two locations


Please advise.

If this alignment issue is occuring in the 7ft or 9ft long segments as shown in det 8/S8.3.1, then it would be aceptable to align the beam skewed (max. 3/8" as shown in your sketch) to provide CPW. Confirm with Architects and coordinate as necessary that this does not affect metal-stud framing. If the 3/8" skew occurs in 2'9" segment on detail 8/S8.3.1 then relocate the 1/2" thick plates at column web to their designed locations per 13/S8.3.2 and/or 14/S8.3.2 ... Tejas, Crosby Group





New F




Please Reference Increment 1 Drawing S8.3.2, and Increment 2 DSA Stamped Drawing AA2.01 thru AA2.31 On Detail 6 of S8.3.2 there are structural steel members shown to provide a walk way from Science Annex Building 7A to Existing Building 7. There is also a noted that states: 3'-0" (max.) SAD. Referencing the architectural drawing the only information provided is that the passage way is to be 6'-6" wide as stated on AA2.01 and AA2.02. What is the location in respect to gridline A on all floors.
 How far does this walk way extend toward Existing Building 7? Structurals state a MAX not actual dimension.
 What provision are needed to maintain 2 hour rating between building?
 Is there a door on the building 7A side of the fire rating joint? If so please provide door type, quantity, and jamb/header details. 1. See attached linked file. The dimension for locating the two beams for the "bridge" must be determined by the existing location of the fin at building 7 due to the new layout of walls for rooms in the building. The new 2 hour door that will separate the two buildings affect the opening location. We will follow with an ASI to clarify the conditions.

2. The walkway (edge of deck) extends to Bldg 7 and must stop 3" clear of Bldg 7 to allow for seismic movement and the seismic joint. The joint may be required to be installed with Bldg 7 modernization work since a connetion to an opening in Bldg 7 is required to install the opening in Bldg 7 is required to install the joint. The beams are 5' 3" center to center. The edge of the deck and shaft walls in the E/W direction connection the two bldgs is 2 1/2" beyond the center line of the beams. where the 3" seismic separation for movement is required. Details will follow.

4. Although not show in the bridging documents, a 2 hr door will be required. Details will follow. Proposed wall locations in Bldg 7 door size and location.

R. Saiki 3. 2 hour shaft wall systems is required to maintain the 2 hour rating. The seismic joints specificed should have a 2 hour rating Cc: Company Name Contact Name Copies Notes / 5 1/2" OFF (E) FIN OF (E) BLDG.7 (N) SEISMIC FLOOR COVER (E) FIN OF (E) BLDG.7



Bradburn ARCHITECTS LTD. Architecture + Interiors + Planning

Structural
Engineering
728 Mein St.,
Redwood City.
Ca 94063
tal. (650) 367-8100
fox. (650) 367-8189

Hensel Phelps Construction C


ISSUED FOR: DATE: DSA - INC #1 10.21.04

C C E S

DRAWING TITLE BRACE FRAME

DATE: 10.21.04 PROJECT # 04043 SHEET NUMBER


S9.0



Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in any way. If an item in this document is altered, the alteration of the law for any person, unless acting under the direction of the alteration.

Steinberg Group

2




Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in any way. If an item in this document is altered, the alteriang architect, if other than the architect, if other tha

The Steinberg 60 Pierce Avenue San Jose CA 95110 408.295.5446 tel 408.295.5928 fax

SEE RFI 0028 For 30° Angle

Fentress
Bradburn

Structural
Engineering
728 Main St.,
Redwood City,
CA 94063
twl. (650) 367-8100
fax. (650) 367-8189





DSA - INC #1 10.21.04

CS CES


PROJECT # 04043

**REVIEW SET** 






YIELD LINES START AT THE TOP OF FLOOR SALB / THE FLANGE OF BEAM



YIELD LINES START AT THE FLANGE OF COLUMN

CONNECTION DETAIL BF-1C



- HSS BRACE SEE SCHEDULE

YIELD LINES START AT THE FLANGE OF BEAM/THE TOP OF FLOOR SLAB

STIFF. PLATE— TYPE "S3"


HSS BRACE —— SEE SCHEDULE

HSS BRACE — SEE SCHEDULE


GUSSET PLATE "P"—— SEE SCHEDULE

ST'L BM, SEE PLAN

GUSSET PLATE "P" SEE SCHEDULE



YIELD LINE STARTS AT THE TOP OF FLOOR SLAB



YIELD LINE STARTS AT THE FLANGE OF COLUMN

CONNECTION DETAIL BF-1B, BF-1D

TYPICAL NOTES:

1. THE DETAILS PROVIDE GENERAL GUIDELINE FOR BRACE CONNECTION CONFIGURATION ONLY. THE CONTRACTOR SHALL SUBMIT DETAILING SHOP DRAWINGS TO THE ENGINEER FOR REVIEWING AND APPROVAL

BEFORE FABRICATING ALL STEEL COMPONENTS. SEE S9.00 & S9.01 FOR DETAILING PROCEDURE & ADDITIONAL REQUIREMENTS. 2. P, L, A, B, C, D,... ETC. ARE NOTATIONAL VARIABLES TO IDENTIFY BRACE & GUSSET CONNECTION WELD SIZE, LENGTH, ETC. THESE NOTATIONAL VARIABLES ARE UNIQUE AND MAY VARY AT EACH BRACE

CONNECTION. FOR SIZES OF BRACE MEMBERS, GUSSET PLATES "P", WELDING LENGTHS "L", WELDMAN "A", "B", "C", "B", "C" AND "F" SEE BRACE CONNECTION SCHEDULES ON DRAWING SHEETS S6.1. 3. THE WIDTH AND THICKNESS OF STIFFENER PLATE TYPE "S1" SHALL BE SAME AS BRACE MEMBER. WELDING THE STIFFENER PLATE TO THE ADJACENT STEELS WITH DOUBLE SIDES 5/16" FILLET WELDS ALL AROUND.

4. THE WIDTH AND THICKNESS OF STIFFENER PLATE TYPE "S2 SHALL BE AME AS COLUMN FLANGE, WELDING STIFFENER PLATE TO THE ADJACENT STEELS WITH DOUBLE SIDES 5/16" FILLET WELD ALL AROUND.

5. THE WIDTH AND THICKNESS OF STIFFENER TYPE "S3" SHALL BE SAME AS BEAM FLANGE. WELDING STIFFENER PLATE TO THE ADJACENT STEELS WITH DOUBLE SIDES 5/16" FILLET WELD ALL AROUND. 6. FOR BASE PLATE TYPES AND DETAILS, SEE DRAWING SHEETS \$10.11.

7. ALL WELDS SHOWN CAN EITHER BE SHOP OF FIELD WELDS AND ARE AT THE DISCRETION OF THE GENERAL CONTRACTOR.

8. PROVIDE BRACE OVERSLOT REINFORCEMENT PLATE AS SHOWN IN DET. 9/S10.11 (TYP.).

**CONNECTION DETAIL BF-1E** 

Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in any way. If an item in this document is altered, the alteration of the alteration of the alteration.

e E S

DRAWING TITLE BRACE FRAME CONNECTION DETAILS PROJECT # 04043

**REVIEW SET** 

ISSUED FOR: DATE: DSA - INC #1 10.21.04


60 Pierce Avenue San Jose CA 95110 408.295.5446 tel 408.295.5928 fax

Fentress
Bradburn

Structurel
Engineering
728 Main St.,
Redwood City,
CA 94083
tal. (650) 367-8100
fex. (650) 367-8189

Hensel Phelps Construction Cons

SHEET NUMBER



Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in this document is altered, the alteration and the notation "altered by" followed by his signature and the date of such alteration, and a specific description of the alteration.

CONNECTION DETAILS


**REVIEW SET** 

SEE REI 0028 for 30° Angle


Bradburn ARCHITECTS LTD. Architecture • Interiors • Planning 421 Broadway (303) 722-5000 Denver, Colorado 80203 Fax-(303) 722-5080

ISSUED FOR: DATE: DSA - INC #1 10.21.04

SHEET NUMBER




## YIELD LINES START AT THE FLANGE OF BEAM




YIELD LINES START AT THE FACES OF COLUMN

CONNECTION DETAIL BF-2C




## YIELD LINES START AT THE FLANGE OF BEAM




YIELD LINES START AT THE CENTER LINE OF GUSSET PLATE

CONNECTION DETAIL BF-1B, BF-2A, BF-1D, BF-3A



YIELD LINE STARTS AT THE FLANGE OF BEAM



YIELD LINE STARTS AT THE FLANGE OF COLUMN

CONNECTION DETAIL BF-1C, BF-1E

1. THE DETAILS PROVIDE GENERAL GUIDELINE FOR BRACE CONNECTION CONFIGURATION ONLY. THE CONTRACTOR SHALL SUBMIT DETAILING SHOP DRAWINGS TO THE ENGINEER FOR REVIEWING AND APPROVAL BEFORE FABRICATING ALL STEEL COMPONENTS. SEE S9.00 & S9.01 FOR DETAILING PROCEDURE & ADDITIONAL REQUIREMENTS.

2. P, L, A, B, C, D,... ETC. ARE NOTATIONAL VARIABLES TO IDENTIFY BRACE & GUSSET CONNECTION WELD SIZE, LENGTH, ETC. THESE NOTATIONAL VARIABLES ARE UNIQUE AND MAY VARY AT EACH BRACE CONNECTION. FOR SIZES OF BRACE MEMBERS, GUSSET PLATES "P", WELDING LENGTHS "L", WELDMAN "A", "B", "C", "B", "C" AND "F" SEE BRACE CONNECTION SCHEDULES ON DRAWING SHEETS S6.1.

3. THE WIDTH AND THICKNESS OF STIFFENER PLATE TYPE "S1" SHALL BE SAME AS BRACE MEMBER. WELDING THE STIFFENER PLATE TO THE ADJACENT STEELS WITH DOUBLE SIDES 5/16" FILLET WELDS ALL AROUND.

Warning: It is a violation of the law for any person, unless acting under the direction of a licensed architect, to alter an item in any way. If an item in this document is altered by followed by his signature and the date of such alteration, and a specific description of the alteration.

4. THE WIDTH AND THICKNESS OF STIFFENER PLATE TYPE "S2 SHALL BE AME AS COLUMN FLANGE, WELDING STIFFENER PLATE TO THE ADJACENT STEELS WITH DOUBLE SIDES 5/16" FILLET WELD ALL AROUND.

5. THE WIDTH AND THICKNESS OF STIFFENER TYPE "S3" SHALL BE SAME AS BEAM FLANGE. WELDING STIFFENER PLATE TO THE ADJACENT STEELS WITH DOUBLE SIDES 5/16" FILLET WELD ALL AROUND.

6. FOR BASE PLATE TYPES AND DETAILS, SEE DRAWING SHEETS \$10.11.

7. ALL WELDS SHOWN CAN EITHER BE SHOP OF FIELD WELDS AND ARE AT THE DISCRETION OF THE GENERAL CONTRACTOR.

8. PROVIDE BRACE OVERSLOT REINFORCEMENT PLATE AS SHOWN IN DET. 9/S10.11 (TYP.).

Es Es

BRACE FRAME CONNECTION DETAILS

DRAWING TITLE

DATE: 10.21.04 PROJECT # 04043 SHEET NUMBER

**REVIEW SET** 

Fentress
Bradburn

ARCHITECTS LTD.


Architecture • Interiors • Planning


Structural
Engineering
726 Main St.,
Redwood City.
CA 94063
group


Structural
Engineering
726 Main St.,
Redwood City.
CA 94063
60. (650) 367–8100
fox. (650) 367–8189


Hensel Phelps Construction C


DSA - INC #1 10.21.04













2"x20 GA. METAL DECK——— OVER 2 1/2" LT. WT. CONC. SEE NOTE #8 SHT. SA2.02 THIRD FLOOR PLAN





FIRST FLOOR PLAN

3 SCALE: 1/4" = 1'-0"

REVIEW SET


60 Pierce Avenue San Jose CA 95110 408.295.5446 tel 408.295.5928 fax

Fentress
Bradburn

ARCHITECTS LTD.

Architecture • Interiors • Planning

421 Broadway (303) 722-5000 Denver, Colorado 80203 Fax-(303) 722-3080



COLLEGE SKYLNE

ISSUED FOR: DATE:
DSA - INC #1 10.21.04

DRAWING TITLE BUILDING A-STAIR #1 & #2 PLANS

DATE: 10.21.04 PROJECT # 04043 SHEET NUMBER S11.1

